

# 2012-2014 Rockford Speedway Rules & Specifications

## TABLE OF CONTENTS

<b>TABLE of CONTENTS .....</b>	<b>1</b>
<b>FORWARD .....</b>	<b>2</b>
<b>SECTION 1 - GENERAL RULES .....</b>	<b>2</b>
<b>SECTION 2 - BENEFITS &amp; INSURANCE .....</b>	<b>4</b>
<b>SECTION 3 - GENERAL POLICY .....</b>	<b>5</b>
<b>SECTION 4 - PROTEST &amp; INSPECTION .....</b>	<b>8</b>
<b>SECTION 5 - REGISTRATION .....</b>	<b>10</b>
<b>SECTION 6 - TRACK RENTAL .....</b>	<b>11</b>
<b>SECTION 7 - MINIMUM SPECIFICATIONS .....</b>	<b>12</b>
<b>SECTION 8 - SPECIFICATIONS INDEX .....</b>	<b>16</b>
<b>NASCAR American Short Trackers .....</b>	<b>17</b>
<b>NASCAR All-American Sportsman .....</b>	<b>24</b>
<b>NASCAR Late Models .....</b>	<b>30</b>
<b>NASCAR Roadrunners .....</b>	<b>34</b>
<b>Winged Women on Wheels .....</b>	<b>40</b>
<b>Figure 8 .....</b>	<b>40</b>
<b>Hornets .....</b>	<b>41</b>
<b>Flag Rules .....</b>	<b>42</b>
<b>Roll Bar Diagrams .....</b>	<b>45</b>
<b>Notes / Amendments</b>	<b>last page</b>

### **FORWARD**

Rockford Speedway has provided over a half century of highly competitive racing entertainment to auto racing enthusiasts across the Midwest. The same high goals set in 1948 for competition is preserved by presenting a "level" playing field for competitors from the entry-level divisions to the Late Model division. These goals have been reached with this rulebook by using innovative ideas, affordable racing and fair enforcement. The management, R.A.C.E. staff and NASCAR officials, with a determined dedication to racing, will use their best efforts throughout the season to keep the standards of racing at Rockford Speedway high.

There have been many changes over the past seasons. We want this year to be a landmark year for the Rockford Speedway and YOU are the biggest part.

The Deery Family, NASCAR Officials and the Rockford Speedway staff wish you a successful, fun and a rewarding career of racing. Thank You.

Jody Deery  
Promoter/CEO  
Rockford Speedway, Inc.

### **PROMOTIONAL RELEASE**

Any competitor who wishes to compete, consents to the use of his name, pictures of himself and car for publicity. Advertising and endorsements both before and after the racing events, and relinquishes any rights to photos taken in connection with events and consents to the publication or sale of such photos as the speedway management so desires.

### **ROCKFORD SPEEDWAY INC.**

P.O. Box 1000, Rockford, IL 61105-1000

9572 Forest Hills Road, Loves Park, IL 61111

**24 hour Race Hotline:** 815.633.1500      **Business offices:** 815.633.0735 / 815.633.0063

**Fax:** 815.654.8360

**E-mail:** rockfordgregg@lycos.com      www.RockfordSpeedway.com

## **SECTION 1 GENERAL RULES**

### **1. APPLICATION**

- 1.1 This general rules section applies to each and every racer, mechanic and / or all pit personnel. Some items, obviously, do not apply to each class. You can easily determine which rules do not apply to you. You are expected to know the rules. Ignorance will not be tolerated as an excuse.

### **2. COMPETITOR OBLIGATIONS**

- 2.1 Every driver must inspect the racing surface and race track area to learn of any defects, obstructions, or anything which, in his opinion, is unsafe and shall report that condition in writing, to the Director of Competition. Any driver entering any racing event is considered to have inspected the track and all conditions are satisfactory to him. If not, *driver should not race*. The participant indicates that he is aware that auto racing involves risks and assumes these risks with full awareness and knowledge.

### **3. GENERAL STATEMENT**

- .1 The rules and regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum requirements for such racing events. These rules shall govern the condition of all Rockford Speedway events, and by participating in these events, participants are deemed to have complied with these

rules. No express or implied warranty of safety shall result from publication of, or compliance with these rules and / or regulations. They are intended as a guide for the conduct of the port and are in no way a guarantee against injury or death to participants, spectators, or others. The official in charge shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. *No expressed or implied warranty of safety shall result from such alteration of specifications.* Any interpretation or deviation of these rules is left to the discretion of the officials in charge. Their decision is final.

#### **4. CONDUCT**

- 4.1 Any fighting or reckless driving in the Pit area may subject the offender to suspension depending on the seriousness of the incident and the decision of the Management. Continuing problems from the same individual will result in permanent suspension. A fine greater than \$100.00 may be assessed to participant or participants of a fight.
- 4.2 We demand courteous conduct from all participants at all times. We will not tolerate profanity in front of race fans or Officials or Management. Profane signs on your car, sex signs, swastikas or Nazi symbols on your car or clothes, unusual dress or hairstyles are not allowed. We expect you to look like a professional and act like one! Be clean, uniformed and look respectable.
- 4.3 Penalties and fines for violation of the conduct, race procedure, and general rules may be implemented per the NASCAR Rule Book to all participants (NASCAR members and non members) at the discretion of the officials.
- 4.4 At any time the display of any type of weapon or threat of bodily harm will result in permanent suspension for the entire racing crew and will result in arrest of all parties involved.
- 4.5 Every racer is expected to participate in every event that it's possible for him to run. By refusing to participate because of disagreement with the length, type, or style of the race, racer is subject to suspension by Management.

#### **5. TRACK POLICY:**

*IMPORTANT NOTICE TO ALL PERSONNEL:*

- 5.1 Rockford Speedway is private property.  
Any person on this property without the expressed permission of Rockford Speedway, it's owners or management is guilty of trespass and subject to the penalties prescribed by law. Through your NASCAR license and registration, you have been given the authority and the right to be on this property in conjunction with racing activities. However, the Administration of Rockford Speedway reserves the right to revoke and cancel this authority at any time that it is felt that your presence or conduct is not in the best interest of the sport of auto racing, fellow competitors, the fans, staff and management of Rockford Speedway.

## **SECTION 2**

### **BENEFITS & INSURANCE**

#### **1 PARTICIPANT BENEFITS**

- 1.1 Posted in Pit Office is a certificate of benefits which applies to everyone signed into the Pits. You and your crew members are covered with benefits as described by the certificate. Contact Rockford Speedway management with any questions or problems regarding benefits.
- 1.2 All competitors, crews and persons are encouraged to be a current member of NASCAR to gain entrance to the restricted pit areas.

#### **2 BENEFIT PLAN**

- 2.1 Each participant with a competitor permit, and who has signed the release sheet for the Event for which the competitor permit is issued, is eligible to be entitled to benefits if he is accidentally injured while participating in said Event. All competitors agree to abide by the decisions of the Benefit Plan officials in administering the Benefit Plan. The Benefit Plan applies only at Events and not while in route to or from an Event.
- 2.2 Benefit questions must be presented in a timely manner.
- 2.3 We recommend that you familiarize yourself with available benefits.
- 2.4 It is the participants' responsibility to understand the waiver and release. Any and all questions, misunderstandings and concerns should be addressed before participant signs the waiver and release forms.
- 2.5 Competitor or pit permits are not transferable and are not to be signed by anyone except the person to whom issued.
- 2.6 Any transfer of competitor permits will result in immediate expulsion of offending cars, entire crew and/or persons associated with car.
- 2.7 No participant will be allowed in the pit area until he or she has secured a competitor permit and signed the release sheet for that particular event.
- 2.8 The Speedway assumes no responsibility for damage to or loss of your equipment, vehicle or any parts by any means.

#### **3 LIABILITY INSURANCE**

- 3.1 Our liability Insurance insures the race track, the car owner, driver and sponsors. (Certificates are available for review by sponsors. Policy reviews and/or additional insured can be arranged at prevailing cost.)
- 3.2 The Speedway assumes no responsibility for damage to or loss of your equipment, vehicle or any parts by any means.

#### **4 MINORS**

- 4.1 MINORS: (14 years through 17 years) Prepare in advance the necessary releases for your parent's or guardian's signature. Don't wait until race day!!
- 4.2 Absolutely no one under 14 will be admitted to pit area.

#### **5 CLAIM INFORMATION**

- 5.1 When involved in an accident involving an injury to you, advise the racing officials immediately so the necessary reporting will be accomplished.
- 5.2 ***NO CLAIMS WILL BE CONSIDERED UNLESS REPORTED PRIOR TO LEAVING THE SPEEDWAY PROPERTY ON DAY OF EVENT.*** Contact the Ambulance driver or Pit Director and give him a full report before you leave the Speedway. If physically unable, your crew must be responsible for this report.
- 5.3 Any participant involved in an accident while on the racing premises and who does not report to an NASCAR Official before leaving the premises will not be eligible for benefits prescribed under the Benefit Plan.
- 5.4 Any participant returning to competition or usual occupation after injury shall be deemed, for the purposes of the Benefit Plan, to be physically fit, and further disability benefits and/or medical benefits shall cease as of that date.

# **SECTION 3 GENERAL POLICY**

## **1 STATE LICENSE REQUIREMENTS**

- 1.1 In order to compete, all race cars, towing vehicles, trailers and/or automotive equipment shall comply fully with all laws concerning motor vehicles.

## **2 PREVAILING POLICY**

- 2.1 The racing officials and management will resolve any disagreement over technical questions or operations. When their decision is rendered, such decision is final and binding.
- 2.2 The Speedway Management and Officials will establish the length, frequency, and administration of all events and programs. Exceptions may be made at the discretion of the Management.
- 2.3 The Management and officials will determine all finishing positions and their decision is final.
- 2.4 Any complaints, disputes, questions or problems must be directed to the Director of Competition immediately following the event.
- 2.5 It is the duty of all drivers, car owners and crew to notify officials of any unsafe equipment, practices or any rule infraction of any car or driver.
- 2.6 Continuous developments in racing may necessitate changes. If necessary, we may update, modify and add to or delete rules. ***The NASCAR "EIRI" (except in rare instances) rule is always in effect and applicable.***
- 2.7 Independent Contractor Status - All Participants are and shall be independent contractors and not agents, servants, or employees. Participants shall use their own methods in performing their duties in accordance with the rules, as obligation to furnish any tools, supplies or materials, which he deems necessary to perform his duties. The participant shall be responsible for compensating, and shall be responsible for all actions of his employees or agents and assumes and takes full responsibility for reporting and paying to the appropriate authorities all charges, premiums and taxes, if any, due and payable on any funds the participant may receive as a result of his duties and/or activities as a participant, including but not limited to social security taxes, unemployment insurance taxes, compensation insurance, income and withholding taxes.
- 2.8 EMERGENCY ACTION: If the act or omission of a Member is determined by an Official or Management to constitute a serious threat to the orderly conduct of the race or racing procedures, that Official may take action against the member. Such emergency action may include ejection from the racetrack and racing premises, suspension of membership and license, or any other action designed to remove the threat created by the member.

## **3 RESTRICTED AREA POLICY**

- 3.1 Full shoes, pants and shirts covering shoulders and torso are recommended at all times in the pit area.
- 3.2 Devices for the purpose of transmitting any radio signals will not be allowed unless specified. The NASCAR confiscation rule will apply.
- 3.3 Possession, consumption or distribution of any alcoholic beverage or controlled substance at any time while in the restricted areas is prohibited.
- 3.4 Officials will use the NASCAR procedure on all participants as it relates to use, distribution or possession of drugs, narcotics or alcohol. By entering the restricted area, all participants agree to accept this policy and procedure. Penalties are determined by NASCAR.
- 3.5 When in the Pit area, maintain a constant watch for your own protection.

## **4 RACE TRACK OPERATING PROCEDURE**

- 4.1 The only people allowed on the racetrack and infield is racing staff & officials. Everyone must stay away at all times unless requested to assist for some special reason. Drivers may seek a place of safety in the infield following disablement. When disabled, stay in your car. Do not remove your helmet or seat belts. Do not get out and examine the damage to your car.
- 4.2 Do not enter the racing surface without expressed authorization an official will O.K. your entry at the track entrance and signal for you to proceed.
- 4.3 Pit crews, owners or personnel related to any car are not allowed on the track at any time.

- 4.4 The track may not be used for practice at any time other than the times designated in these rules. Management will not allow practice except as under the formal track rental agreements.
- 4.5 Any competing vehicle, whose speed has been reduced to a point where it causes a safety issue or retards the track activity, will be removed from the racing surface at the option of the officials.
- 4.6 Our racing program is based on the availability of enough vehicles qualified. If this number is not available, alternative scheduling or programming will be used. Racing events will be "lined up" to accomplish the best racing program.
- 4.7 No driver may get out of his car on the track or infield to argue or discuss the race with any official. If this rule is violated, the driver may be disqualified for the event or suspended according to the decision of the Officials.
- 4.8 Any event is completed when the leader has run over one half of the scheduled length or terminated by the Officials for safety reasons.

## **5 PAYOFF PROCEDURES**

- 5.1 The starting drivers shall earn all points.
- 5.2 All payments will be made to the starting driver. All purse money is paid to the driver only.
- 5.3 Payoff will be made only for events actually completed.
- 5.4 If a program is shortened by rain or by an unforeseeable or fortuitous event, yet 'considered' completed and no rain checks issued, payoff will be made for events completed.
- 5.5 All race results will be announced before, or at, payoff. All winnings will be paid during Payoff.
- 5.6 Payoff is made in cash at the completion of each evening's events at payoff window.
- 5.7 Previous events payoff will be made by check with a \$1.00 check fee deducted at the division's next event at the "Back-pay" window. "Back-pay" window is Window 2 of the main box office. Window opens for 30 minutes immediately following the program.
- 5.8 The driver will receive 1099 tax information.

## **6 TEAM RESPONSIBILITIES**

- 6.1 Any time the conduct of any team member or driver is a discredit to the Speedway, the racing industry or to himself, they will be removed from all racing activity at the Speedway.
- 6.2 The driver is responsible for *all and each* of the people associated with his car and / or signed in with the car.
- 6.3 Responsibilities of the driver and crew are addressed in the NASCAR Rule Book and will prevail in most cases.
- 6.4 Infractions caused by crew members, car owners, family members or associates will result in expulsion of car, driver and entire team for said event.

## **7 DRIVER ELIGIBILITY**

- 7.1 Must possess a NASCAR Drivers License for LM, SP, AST and RR
- 7.2 Must be eligible for State Drivers License.
- 7.3 Must be at least **14** years old for feature division with approval, ages 14-15 may compete in support divisions after undergoing evaluation by Minor's Eligibility Panel
- 7.4 Must be physically fit for racing.
- 7.5 Ages 14 through 17 must file a fully executed and signed minors release to be eligible to compete.
- 7.6 Management reserves the right to accept or deny eligibility to anyone.

## **8 RACE CAR PROCEDURE**

- 8.1 Each car may qualify once. Qualify refers to time trials or qualifying heats, whichever event occurs first.
- 8.2 A driver may swap with a car that has qualified and competed in preliminary events. However, the driver must start in the rear. Driver may improve start position by running qualifying race and/or semi.
- 8.3 Failure to time trial or run preliminary races will exclude car from the feature field. E.I.R.I. will be used when field is less than posted starting number of cars.
- 8.4 Car / driver must run all preliminary events to maintain feature starting position. Exception to this rule based on damage or inability to complete by approval of Director of Competition only.
- 8.5 When available, an alternative to all features will be selected. Order of time trials, finish of preliminary races or top point driver in current point's basis will be used in selection of preliminary races or top point driver in current point basis will be used in selection of alternate.
- 8.6 An alternate starting field car may be selected to join the starting field if a qualified car fails to join the field at "one to go."

- 8.7 A driver may re-time trial an additional car; however doing so disqualifies the first car and time.
- 8.8 The driver who time trials the car must drive it in the racing program, unless approved swap occurs.
- 8.9 No drivers may be relieved without prior approval by track management or the Director of Competition.

## **SECTION 4**

### **PROTEST AND INSPECTION**

#### **1 PROTEST**

- 1.1 Only NASCAR registered car owners and drivers are eligible to file a protest of any kind. The only exception is Roadrunner drivers and car owners may file a protest within their division.
- 1.2 The protest must be filed within 15 minutes following the finish of the event with the NASCAR Director of Competition.
- 1.3 The protest Fee, as described below, in cash, must be deposited with the NASCAR Director of Competition before inspection begins.
- 1.4 On all protests, it is the driver's responsibility to prove his legality, not the Officials' to prove the violation.
- 1.5 The protest fee will be:
  - 1) returned to complainant if subject car is illegal
  - 2) forfeited to Car Owner if subject car is legal.If subject is found to be illegal:
  - 1) Driver forfeits all winnings for that program.
  - 2) Driver forfeits all points for the event. Driver may lose accumulated points in an amount determined by officials.
  - 3) The Driver and/or car may be suspended for a period determined by racing officials.
  - 4) The illegal parts will be confiscated.
- 1.6 The "fee" shall be for a determined protest item and may not be transferred to another complaint. Each protest complaint shall have its own fee.
- 1.7 The following people will be allowed to be present at protest site: car driver, car owner, NASCAR Director of Competition, NASCAR technical supervisors, speedway management, and complainant.
- 1.8 Any decisions, findings, results, changes, corrections or additions will be made subject to conditions at the time subject to approval by Speedway Management. GROUNDS OF COMPLAINT MAY BE OVERRULED BY THE DIRECTOR OF COMPETITION AND/OR ROCKFORD SPEEDWAY MANAGEMENT.
- 1.9 PROTEST FEE SCHEDULE: per item
  - a. \$200.00 -- Internal short block engine inspection.
  - b. \$100.00 -- All other items or protests.
  - c. \$ 50.00 -- Of each fee will be retained by racetrack for the expense of additional administrative time.

#### **2 INSPECTIONS AND PENALTIES**

- 2.1 Competitor Obligations - A competitor must take whatever steps are required, including teardown of the car, as requested by a NASCAR official to facilitate inspection of the car. Failure to submit to inspection, or take all steps requested of inspection shall result in immediate disqualification, suspension of the driver and car owner and/or a cash fine.
- 2.2 All competing cars will be subject to technical inspections every night throughout the season at a time and interval determined by the Director of Competition. No forewarning will be made.
- 2.3 Any car not conforming to the rules will be subject to several method penalties:
  - A. Car may be disqualified, forfeiting all points for the season, plus any moneys earned during the immediate past race meet.
  - B. Points and moneys may be forfeited in the amount and severity decided upon by the Director of Competition.
  - C. Additional weight may be required to be added as determined by the Director of Competition. It may be doubled if the infraction is not corrected by the next race meet. If not corrected by the 3rd meet, the car will be disqualified.
- 2.4 All cars are subject to material inspection by the Officials Workmanship and appearance shall be determining factor to whether Officials permit the car to enter competition.
- 2.5 All parts declared illegal by inspection or protest will be confiscated by R.A.C.E. and NASCAR Officials and disposed of at their discretion.

- 2.6 As an alternative to confiscation of the item, a cash fine may be served. Collected fines will be added to division season point fund. Car and driver may not compete until all fines are paid or parts confiscated.
- 2.7 On all inspections, it is the driver's duty to prove his legality, not the Officials to prove the violation.
- 2.8 During an "inspection teardown" only the following people will be allowed to be present at the protest / inspection site: car owner, car driver, NASCAR Director of Competition, technical supervisors, and speedway management.
- 2.9 ***Speedway management and/or officials reserve the right to impound a car at any time for any reason.***

# **SECTION 5**

## **REGISTRATION INFORMATION**

### **1. DRIVER / CREW** **REGISTRATION**

- 1.1 The Late Model, All-American Sportsman, American Short Tracker, Roadrunner divisions compete under the sanction of NASCAR.
- 1.2 All drivers in these divisions **MUST** be members of NASCAR and R.A.C.E. to be able to compete.
- 1.3 Mechanics, owners and sponsors are required to join NASCAR and R.A.C.E. to receive pit gate fee reduction and plan benefits.
- 1.4 Registration forms are available from Rockford Speedway.

### **2. NUMBER ASSIGNMENT**

- 2.1 We will attempt to reassign all numbers that were taken in previous year to those who had them. "Reassigned numbers" will be held until the preseason registration meeting in February or March.
- 2.2 Walk-in registration will begin immediately following the banquet for previous year registered drivers. Drivers may pay all fees and register their previous year car number.
- 2.3 At the registration meeting, all and any unassigned numbers become available to anyone. No numbers will be assigned until the vehicle registration form has been received.
- 2.4 Rockford Speedway management reserves the right to assign, award or dictate number assignments.
- 2.5 Champions may have No. 1 if they desire.

### **3. IDENTIFICATION CARDS**

- 3.1 All registered drivers will receive an official I.D. card that must be presented each time when entering the pits to receive pit fee reduction.
- 3.2 No one may participate in race events without being properly registered. **All fees and registrations will be doubled for anyone violating this rule.**
- 3.3 All members of R.A.C.E. must hold a current Membership.
- 3.4 In rare instances, a temporary license may be issued, valid for two weeks, then open rates will be charged.

## **SECTION 6**

# **PRACTICE NIGHTS & TRACK RENTAL**

### **1. PRACTICE NIGHTS**

---

- 1.1 Each Thursday night, when scheduled, open practice sessions from 5: 00 p.m. until sunset are scheduled. Practice allows only one car on the track at any time. Cars are to line up at the track entrance ramp to await their rotation.
- 1.2 **No children under 14 are allowed.**
- 1.3 Parent and guardian must sign minor release for all persons under 18 years old.
- 1.4 Other scheduling and or speedway business may preempt practice days.

### **2. TRACK RENTALS**

---

- 2.1 The track is available for use at other times. Call track office for availability and reservation. Must reserve track rental time at least seven days in advance. NO Rentals on event day.
- 2.2 Rental times are 9 am till noon; noon till 3 p.m.; 3 p.m. till 6 p.m.
- 2.3 **Rental fee is \$200.00 for 3 hour time slot, per car for non R.A.C.E. members**
- 2.4 **Rental fee is \$75.00 for 3 hour time slot, per car for R.A.C.E. members.**
- 2.5 A \$25 “clean-up” deposit will be charged at sign-in and returned only if area is in like manner at completion of rental.
- .6 Rental times and rates are subject to change.
- 2.7 Multiple cars will be allowed during a track rental session, however only one car on track at a time. Fees will be charged on a per car basis.
- .8 “Rain checks” are not issued for any reason.
- .9 All individuals must sign a Waiver and Release prior to entering restricted areas.

# SECTION 7

## MINIMUM SPECIFICATIONS

Rockford Speedway will compete under the sanctions of NASCAR. The specifications listed will become part of the Official NASCAR Rule Book, except in cases of obvious conflict. All technical rules will generally fall within NASCAR and R.A.C.E. specifications. Any disputes will be resolved by NASCAR and R.A.C.E. officials.

### 1 GENERAL

- 1.1 At any time, before, during or after an event, officials may require additional measures or equipment or make additional determinations, as they deem necessary to further reduce the risk to competitors.
- 1.2 All cars are subject to a minimum specification inspection at any time. It is the responsibility of the driver to prepare each car FREE of defects and in safe racing condition.
- 1.3 A quick release type approved safety belt of no less than three (3) inches in width is mandatory. Both ends must be fastened to roll bar cage with aircraft quality bolts not less than 3/8 of an inch in diameter. A steel plate may be welded to the roll bar cage on the right side of the driver so the belt can be brought down in such a manner that it will prevent the driver from sliding from side to side under the belt. The belt must come from behind the driver. Shoulder harness inertia reel not allowed. Belts must show manufacturer's production date within two years for LM, **SP**, AST and three years for RR, WWOW, Figure 8, **Bandits** and Hornets.
- 1.4 A padded head restraint with approved installation recommended.
- 1.5 Hans or Hutchins II device is highly recommended for all participants.
- 1.6 Center top of steering post must be padded with at least two inches of resilient material.
- 1.7 All cars must have approved five pound or greater fire extinguisher.
- 1.8 Each pit crew should have an approved fire extinguisher in ready reach for any emergency.
- 1.9 All competitors' helmets must meet the specifications set forth in Title 49, Code of Federal Regulations, Part 571, Federal Motor Vehicle Safety Standard Number 571.218 or meet the specifications, in ANSI A90.1-1971, ANSI Z90.1a-1973 and ANSI Z90.1b-1979, and meet SNELL minimums. **Minimum SNELL SA-2005 rating required, SNELL 2010 Remommended.**
- 1.10 Driver's seat must be fastened to the frame and must be located a minimum of eight (8) inches from the inside of the closest driver's door bar.
  - a) Rib rest shall remain flexible, not reinforced.
  - b) No fiberglass seats.
- 1.11 **Flame-retardant gloves are mandatory in all divisions, to be worn at all times on track.**
  - A. \$25.00 fine for first violation.
  - B. \$50.00 fine for second violation.
  - C. Suspension for third violation.
- 1.12 Window nets are required and must be used at all times. "Quick release" method of mounting is mandatory. Window net must be approved ribbon or mesh type. Window net must "fall down" when released. Helmet right side nets recommended.
- 1.13 All drivers must be protected at all times, including practice, with a recommended flame resistant driving suit of 2 piece top & bottom or undergarments.
- 1.14 **RECOMMENDED INDIVIDUAL PERSONAL PROTECTION**

<input checked="" type="checkbox"/> On board fire system with 2 nozzles	<input checked="" type="checkbox"/> Neck collar
<input checked="" type="checkbox"/> Single layer suit with complete underwear	<input checked="" type="checkbox"/> Full face helmet
<input checked="" type="checkbox"/> Multiple layer driver suit	<input checked="" type="checkbox"/> Racing seat head rest
<input checked="" type="checkbox"/> Nomex driving shoes	<input checked="" type="checkbox"/> High density roll bar padding
<input checked="" type="checkbox"/> Nomex socks	<input checked="" type="checkbox"/> Cage "helmet" net
<input checked="" type="checkbox"/> HANS or Hutchins II device	<input checked="" type="checkbox"/> Collapsible steering column
<input checked="" type="checkbox"/> Approved sternum harness	<input checked="" type="checkbox"/> Collapsible steering wheel

## **2 BATTERY MOUNTING MASTER CONTROL SWITCH**

- 2.0 12-volt single battery systems only. Dry Cell highly recommended.
- 2.1 Battery must be securely mounted and covered.
- 2.2 Battery must be located within the frame rails and forward of rear axle.
- 2.3 Master on-off switch required ground side.
  - A. Late Models and All-American Sportsman mounted within reach from outside driver's door.
  - B. American Short Trackers - on driver's side cowl panel, in reach from outside race car.

Exception: See BANDITS>

## **3 FUEL REQUIREMENTS**

- 3.1 Fuel cells must be separated from the driver's compartment by a full, complete metal firewall.
- 3.2 Fuel cells must be securely mounted between the frame rails and behind the rear end. Fuel cell must be adequately protected from behind and below by a triangularly braced fuel tank guard.
  - a) Minimum of two (2) 1 ½" x 1/8" straps under and over fuel cell.
- 3.3 Cell must be protected with 1/8" steel plates on rear, left and right sides.
- 3.4 "Vent tube" must exit out the rear of the car.
- 3.5 Fuel tank must be minimum spec. tank of an outside 18 gauge steel canister, liner of plastic, or suitable rubber, sponge baffles, and boltable filler plate assembly with operable check valves.
- 3.6 Maximum capacity of fuel tank: 22 gallon.
- 3.7 Lowest point of the fuel tank and assembly must be minimum of 10" from ground on Late Model and AST cars.
- 3.8 10" minimum on all All-American Sportsman cars, from the ground. All-American Sportsman may use 2 - 1" square tubing for fuel tank support.
- 3.9 Roadrunners, NF8L, and WWoW, Bandits may utilize an approved fuel container as an alternative to a fuel cell. Maximum capacity of 6 gallons must be mounted above trunk floor.
- 3.10 Fuel filler may not be mounted to body.
- 3.11 No electric fuel pumps. (exception 3.12)
- 3.12 American Short Trackers may use an electric fuel pump provided an on/off switch is within easy reach of the driver and labeled. Hornets/Bandits, WWOW may use stock electric fuel pump.
- 3.13 No pressure fuel systems except Bandits, Hornets, WWOW
- 3.14 Absolutely no use of nitrous oxide or NO2 injectors will be allowed.
- 3.15 Regularly available pump gas or Racing Gasoline only as a fuel, no fuel additives allowed.
- 3.16 Fuel specifications violations will result in a cash fine of \$300.00 minimum to \$500.00 maximum.
- 3.17 Fuel must meet properties of track pump fuel.**

## **4 CAR APPEARANCE AND LETTERING**

- 4.1 Professional lettering and painting are required. All race cars must be neat appearing with a good paint job. The car number must be at least 18" or more in height and appear on both doors of the car in a **contrasting** color. This means the number must be significantly darker or lighter than the base color, not just different. Numbers should be easily readable from 100 yards.
- 4.2 Cars must display roof numbers 30" high, readable from the right side for scoring.
- 4.3 Gold, silver, or foil number decals are permitted

- 4.4 The driver's last name and car number, a 4" minimum letter height, must be displayed on windshield, with car number on front headlight door and rear deck lid.
- 4.5 Series decal locations are mandatory as shown prescribed by technical bulletin. All purse moneys will be forfeited if car does not comply with all decal and patch locations.
- 4.6 The hood must be in place for all events unless approved by Speedway official.
- 4.7 No "For Sale" signs on cars while racing.
- 4.8 No decals with questionable language, symbols or signs.
- 4.9 Dark color paint schemes are discouraged.

## **5 MUFFLERS**

- 5.1 All competing cars, in all divisions, at all times, must have a muffler or restrictor device that meets minimum specifications of 100 decibels @ 100'.
- 5.2 Muffler or restrictor device must be easily removed, not welded.

## **6 WEIGHT**

- 6.1 All weight measurements, including minimums, will be made with the driver sitting in the driver's seat, with steering wheel in place, hands on steering wheel and helmet on driver's head.
- 6.2 All "added" weight must be mounted to FRAME or UNIBODY STRUCTURE. Consult division guidelines in this book. Do not mount to firewall, floor pan, or within driver's compartment.
- 6.3 Minimum weight units - 5 lb.
- 6.4 All ballast weight will be painted white and numbered to car. \$25 fine for each piece that fails to comply.
- 6.5 Any loss of weight from any car for any reason, will result in a cash fine of \$25.00 for 1st offense, \$100.00 for every occurrence thereafter.
- 6.6 Ballast weight must meet 10" ground clearance behind rear axle.
- 6.7 Weight determined by the official Rockford Speedway scales only.

## **7 MATERIALS**

- 7.1 No ceramic components or chemical coatings allowed in engine internal areas of intake manifold, exhaust manifold and cylinder heads, engine oiling system, drive train or suspension.
  - a) Ceramic piston coating is permitted.
- 7.2 No carbon fiber components or coated products allowed. (Helmet material acceptable as a helmet only.)

## **8 TRACK TIRE RULE**

### **LATE MODELS**

- 8.1 A team may purchase only one tire per night, per car.
- 8.2 Tires will be plated with a unique symbol.
  - Teams may purchase tires from other teams, however, purchased tires will be treated as a NEW tire(s).
- 8.4 NEW cut or damaged tires may be replaced if tire has code for that night, providing tire has not completed one half of the feature laps. Damaged tire must be inspected by Director of Competition to approve new tire for following week.
- 8.5 Teams may purchase **eight** new tires on or before first night of competition. Teams may purchase one new tire on third night of competition. One tire per night there after.
- 8.6 Tires follow the driver, not the car. (NOTE: Some exceptions may apply, but only with the approval of the Director of Competition.)
- 8.7 Penalties – Penalties subject to discretion of officials.
- 8.8 'USED' tires may be utilized in place of 'NEW' tires, however they will be counted against your allowed 'NEW' tires.
- 8.9 Cars participating in the semi feature are eligible for a new tire the following week, if they completed all laps in race.
- 8.10 Speedway officials and management may make amendments or changes to these rules at anytime.

## SPORTSMAN AND AMERICAN SHORT TRACKERS

*Same rules apply as the Late Models with the following exceptions*

- 8.13 Teams may purchase a tire every second night of competition.
- 8.14 Teams may only purchase **six** new tires prior to the season start.
- 8.15 Multiple replacement tires (damaged, etc.) allowed only with Director of Competition's approval.

## **9 MISCELLANEOUS**

- 9.1 One-way receivers are required in the Late Models, American Short Tracker, Sportsman, RoadRunners, Figure 8, Winged Women, Bandit, Hornet divisions. Receivers must receive Race Control frequency 469.8750 (Raceceiver/SOLO II channel 1591.)
- 9.2 Instead of a receiver, radios allowed in the Late Model division only. If using a radio, driver must provide a spotter in designated Spotter area **and driver must also monitor** race control frequency. Any other use will result in confiscation of equipment and a cash fine. All frequencies must be registered with Officials before competition.
- 9.3 Appearance of pit personnel must be neat and clean. Remember -- your appearance and manner is a visual statement for your sponsors and fans.
- 9.4 Rockford Speedway Identification Patch must be displayed on all drivers' uniforms. It must be located above "chest pocket" area on either side.
- 9.5 "Series" sponsor patches may be required on your uniform.
- 9.6 Only one center mounted inside mirror. No outside mirrors except left "spot" mirror allowed. Cannot be mounted outside.) A 4-panel maximum wink mirror allowed.
- 9.7 Tow hook on front and rear required. Front hook may be under hood. Tow hooks must be clearly marked with a 3" arrow of contrasting color. Must be made of chain or heavy cable thicker than .25".
- 9.8 Suspension components including stabilizer bar may not be adjustable from the driving compartment
- 9.9 **ILLEGAL EQUIPMENT includes but is not limited to-** Nitrous or other injection systems, electric fuel systems, multi-coil, data acquisition, electronic traction-control devices.
- 9.10 Antifreeze not permitted. First offense: 1-week suspension.
- 9.11 "Stupid" leaking will result in the following fines:
  - A. \$25.00 first offense.
  - B. \$50.00 second offense.
- 9.12 Rookie drivers may display indication of such.
- 9.13 All prices for approved parts listed are at current pricing.
- 9.14 If the rules don't say you can do it-don't do it.



## **SECTION 8**

### **SPECIFICATIONS SECTION INDEX**

Wheelbase, Eligible Models	1
Body & Appearance	2
Windshield/Glass	3

### **DETAILED ENGINE REQUIREMENTS**

Location	4
Origin	5
Engine Displacement	6
Engine Block	7
Engine Pistons/Rods	8
Oil Pans/Oil Systems	9
Crankshaft & Balancer	10
Cylinder Heads	11
Intake Manifold	12
Camshaft, Valve Lifters & Rocker Arms	13
Compression/Pistons	14
Exhaust	15
Carburetor	16
Carb Spacers, Gaskets & Mounting	17
Air Intake	18
Fuel Systems	19
Electrical Systems	20
Cooling Systems	21
Clutch	22
Transmission	23
Differential	24
Driveline	25
Brakes	26
Frames	27
Rollbars	28
Suspension	29
Spindles/Hubs	30
Steering	31
Ground Clearance	32
Wheels	33
Tires	34
Weight	35
Gas Tank Installation	36
Personal Protection Requirements	37
Eligibility	38
General Policy	39
Number & Appearance	40
Types of Racing Events	41
Claim Rules	42

# NASCAR

## American Short Trackers

This Rockford Speedway Division will compete under the *sanctions* of NASCAR. The specifications listed will become part of the official NASCAR Rule Book, except in cases of obvious conflict. All technical rules will generally fall within NASCAR and R.A.C.E. specifications. Any disputes will be resolved by NASCAR officials. All drivers in this division must be members of NASCAR and R.A.C.E. to complete.

### NOTICE

All equipment is subject to the approval of NASCAR officials. No equipment will be considered as having been approved by reason of having passed through inspection unobserved. Any equipment which does not conform to specifications or tolerances contained in this NASCAR rule book, will not be eligible for approval.

### 1 WHEEL BASES AND ELIGIBLE MODELS

- 1.1 1994 and older American produced 94" to 103" stock wheelbase have been approved for competition. Wheelbase must be stock for chassis (+ or - ½ inch)
- 1.2 Maximum track width 63 ½" inches (1/2" tolerance)

### 2 BODY AND APPEARANCE

- 2.1 All cars must be stock appearing with bodies, fenders, bumpers and trunks in proper configuration and symmetrical as produced for make and model.
- 2.3 Door panels, may be replaced with 22 gauge minimum metal skins that meet stock configuration, size and appearance.
- 2.4 No substitutes for steel except door panels and hood.
- 2.5 Approved after-market nose and tailpieces that follow original body configuration permitted.
- 2.6 Openings in the body, fenders and rear created by the removal of lights, door handles and accessories must be covered by solid metal.
- 2.7 Stock appearing hood with no air scoops, holes, vents, ducts or openings in hood.
- 2.8 Hood must be rear-hinged and secured by hood pins (minimum of 2).
- 2.9 No aerodynamic devices to modify air flow. Front lower spoiler or "air dam" is acceptable, provided they do not protrude forward of the bumper and meet 5-inch ride height minimum.
- 2.10 Tires may not protrude over two inches (2") from the original body configuration. Fender wheel wells may be "flared" for tire clearance while maintaining proper body configuration.
- 2.11 Side window door openings must maintain stock size and configuration. All side windows must remain open except for window net. Posts must remain in stock location and stock size. Rear quarter glass openings must be covered with clear Lexan or left open.
- 2.12 A single spoiler may be used, mounted on the rear trailing edge of the stock trunk or hatch. Single plane spoiler and lip may not exceed 5 inches in total height. Width may not exceed, and must follow, rear trailing edge of deck.

### 3 WINDSHIELDS AND GLASS

- 3.1 Windshield and rear window mandatory with minimum 1/8" clear Lexan only.
- 3.2 Rear window must be single piece with allowance for two (2) one inch holes for wedge bolt adjustment.
- 3.3 Minimum of 2 center braces, at stock angle, required on front and rear windows.
- 3.4 Front windshield opening and rear window opening must maintain stock factory size, configuration and angle (degree).
- 3.5 No tinted windows allowed.

### 4 ENGINE LOCATION

- 4.1 The engine must remain in stock location.
- 4.2 Side to side lateral location must be within one inch (1") of the centerline of front frame rails.
- 4.3 Transmission and transmission cross member must remain in stock mounting brackets.

### 5 ORIGIN

- 5.1 Origin must be GM, Ford or Chrysler.
- 5.2 Engine must match chassis.
- 6. ENGINE DISPLACEMENT**
- 6.1 Approved 4 cylinder in-line engines with maximum displacements and maximum overbore:
  - A. Ford - 2000 (.060), 2300 (.060)
  - B. Chrysler - 2200 (.050)
  - C. GM - 2000 (0.60)
  - D. GM - 2300 (.030)
  - E. GM - 2500 (.030)
- 7. ENGINE BLOCK**
- 7.1 Must be of standard factory production with standard external measurements in all respects.
- 7.2 Iron sleeves may be added to block.
- 8. ENGINE PISTONS / RODS**
- 8.1 Steel connecting rod with stock stroke crank.
- 8.2 No titanium or stainless steel connecting rods.
- 8.3 Any flat top piston without modification except minor valve relief.
- 8.4 GM Production engines will be allowed to run domed pistons on a trial basis.
- 9. OIL PANS/OIL SYSTEMS**
- 9.1 Increased capacity oil pans are allowed.
- 9.2 No external oil pumps or dry sump systems.
- 9.3 No oil coolers.
- 10. CRANKSHAFT**
- 10.1 Any production crankshaft, cast iron, steel or billet steel material, with stock stroke for that engine allowed.
- 11. CYLINDER HEADS**
- 11.1 All cylinder heads are subject to approval.
- 11.2 Cylinder heads must be a stock OEM produced approved casting.
- 11.3 No after-market or fuel injected heads.
- 11.4 The cylinder heads must be completely cast iron or aluminum in stock application.
- 11.5 The intake and exhaust ports and runners must be in the original "as cast" configuration.
- 11.6 Zero tolerance of any evidence of sanding, grinding, polishing, relieving, alterations, porting, chemical treating, coating or altering the original form of ports, runners or combustion chambers.
- 11.7 The valves must be stock size & in stock location.
- 11.8 Combustion chambers may be "cc" matched by reseating valves only.
- 11.9 The maximum angle allowed of any valve job cut in relationship to matching of valve and seat will be 75 degrees.
- 11.10 Intake gasket and head gasket surfaces may be remachined (milled) to improve sealing.
- 11.11 Any style valve springs and retainers allowed.
- 11.12 Valve guide material optional.
- 11.13 Valve angle must remain within two (2) degrees of factory-produced angles.
- 11.14 No titanium parts in valve train-except retainers.
- 12. INTAKE MANIFOLD**
- 12.1 All engines must have stock, unaltered approved production single carburetor, intake manifolds. No alterations of any type permitted to manifold except:
  - a) EGR Hole must be plugged.
  - b) Water Jacket may be welded shut.
- 12.2 On all engines, only one standard, stock flat gasket may be used between the head and the intake manifold. No wedge type gaskets allowed. No metal or Bakelite spacers allowed.
- 13. CAMSHAFT / VALVE LIFTERS AND ROCKER ARMS**
- 13.1 Only steel flat tappet camshafts are permitted. No roller cams, no hard faced overlay cams.
- 13.2 No automatic cam timing devices allowed.
- 13.3 Camshaft bearings must remain stock type babbit.

- 13.4 Stock rocker arms only, no roller rockers. Roller rockers permitted in push rod engines only.
- 13.5 No titanium parts allowed.
- 14. COMPRESSION**
- 14.1 No compression limit has been set at this time, but is under review.
- 15. EXHAUST**
- 15.1 Any type exhaust system permitted.
- 15.2 Exhaust maximum of 2.5 inch I.D. from end of collector to exhaust pipe exit.
- 15.3 Exhaust pipe from collector to end of exhaust pipe must be a minimum length of 48 inches, including muffler. Exhaust pipe must be attached to collector at all times with no leaks.
- 15.4 Entire exhaust system must be outside driver's compartment, under car and in front of firewall. Exhaust must exit underneath the car, pointing downward.
- 15.5 Muffler device (100 decibels @ 100 feet) is required.
- 15.6 Exhaust pipe must be securely mounted to the bottom of chassis.
- 16. CARBURETOR**
- 16.1 Carburetors allowed are the NASCAR approved Holley 2300 HP 2bbl, part #7448 and the Holley 300 HP 2bbl, part #80787-1, with a venturi size of 1 3/16" and maintaining a throttle bore maximum size of 1-1/2". Only Holley replacements parts can be used in any carburetor rework.
- 16.2 CARBURETOR REWORK GUIDELINES: MAIN BODY:** Reshaping polishing, grinding, or drilling of additional holes will not be permitted. The maximum size for the air bleed holes in the top of the carburetor body will be 0.080 inch for all 4 holes. Screw in air bleed jets will not permitted in the 2300 main body. Screw in air bleed jets will be permitted in the 2300 HP main body but must be epoxied in place. For the Holley 2300 HP main body, the amount of holes and passages must remain as manufactured. Additional and/or plugging holes or passages will not be permitted in the Holley HP 2300 main body.
- 16.3 The choke may be removed, but all screw holes must be permanently sealed.
- 16.4 The booster type must not be changed. The Holley booster part number 45R-107-1, with the casting number 45R-107 and part number 45R-312R, with the casting number 45R-312 are the only boosters that will be permitted. The Holley casting numbers must remain legible on the top of all booster stems. Size or shape must not be altered. Height and location of the boosters must remain as manufactured. All boosters must maintain a minimum outside diameter of 0.616 inch. The addition of material will not be permitted to the boosters with the exception of a small amount of epoxy which may be used to assist in securing the booster stem to the main body of the carburetor.
- 16.5 The venturi area must not be altered or reshaped in any manner. The venturi must remain completely round. The casting ring must not be removed. The location of the venturi must remain as produced by the manufacturer. By judgment of officials, any alterations that were made to allow additional air to be picked up below the opening of the venturi such as altered gaskets, base plates and drilling holes into the carburetor will not be permitted.
- 16.6 The carburetor throttle body must be used as provided by the manufacturer. The positioning of the throttle bores in the carburetor throttle body must be the same as provided by the manufacturer. The throttle bores must be completely round and must remain perpendicular to the top and bottom of the carburetor throttle body. The throttle body (base plate) must not be altered in shape or size. All vacuum holes must be threaded and plugged.
- 16.7 Stock throttle plates must not be thinned or tapered. Idle holes may be drilled in butterflies. Screw ends may be cut even with the shafts, but the screw heads must remain standard.
- 16.8 Throttle shafts must remain stock and must not be thinned or cut in any manner.
- 16.9 Only Holley metering blocks can be used. Surfacing of the metering blocks for improved gasket seal will be permitted. The only metering blocks permitted for the Holley 2300 HP carburetor (80787-1) will be the Holley part numbers 11938N, 11886 and 12323 metering blocks. For the Holley 2300 HP approved metering blocks, the amount of holes and passages and the location must remain as manufactured, however holes sizes may be altered. Additional holes or passages will not be permitted in the Holley 2300 HP approved metering blocks. The Holley metering block, part number 12323 will not be permitted in the Holley 2300, list number 7448.
- 16.10 The accelerator pump discharge nozzle must not be changed. The retaining screw must not be drilled for a discharge passage.

- 16.11 Power valves and floats may be altered.
- 16.12 Carburetor jets must be the same type as supplied by the manufacturer.
- 17. CARB SPACERS, GASKETS, MOUNTING**
- 17.1 Adapter plate and/or spacer and gaskets may not exceed 1.125 inches.
- 17.2 Adapter plate opening(s) must be straight bored from top to bottom with no taper.
- 17.3 No spacer allowed between air cleaner bottom and carburetor.
- 17.4 Mandatory DOUBLE throttle return springs, working in opposite directions.
- 17.5 No vacuum leaks allowed between air cleaner and intake valves.
- 17.6 Carburetor must be mounted "straight ahead."
- 18. AIR INTAKE**
- 18.1 Stock paper air cleaners only, 3.5" maximum height top to bottom.
- 18.2 No cold air induction boxes of any kind.
- 18.3 No carb "hats" or airflow modification devices.
- 18.4 No air cleaner spacers other than gaskets.
- 18.5 No addition or removal of material to shield or alter airflow to air cleaner allowed.
- 18.6 Bottom lip of air cleaner base may not exceed .75".
- 18.7 Air cleaner top and base must be metal w/o holes.
- 19. FUEL SYSTEMS**
- 19.1 Electrical fuel pumps may be used with a labeled on/off switch is within easy reach of driver.
- 19.2 Fuel lines must be approved by technical inspector if not steel/ steel braided.
- 19.3 No cool cans.
- 19.4 Fuel cell must be fully enclosed from driver's compartment.
- 20. ELECTRICAL**
- 20.1 No magnetos of any kind.
- 20.2 No MSD ignition
- 20.3 "Made for racing" or high performance distributor and coil may not exceed \$400.00.
- 20.4 Dual point distributors permitted.
- 20.5 No programmable or D.I.S. systems.
- 20.6 Ignition firing order must remain as produced.
- 20.7 Alternator must be front of engine mounting only.
- 20.8 Stock production starter for that make and model in original stock position, mount and hardware.
- 20.9 No multiple coil ignition systems. (EIRI)
- 21. COOLING SYSTEM**
- 21.1 Any radiator mounted in front of motor is acceptable. No plastic radiators.
- 21.2 Fan must have a shroud covering 50% of top circumference.
- 21.3 Operational radiator overflow catch can and exit tube must be mounted and permanently installed ahead of firewall.
- 21.4 Electrical fans for cooling radiator are acceptable providing manual on/off switch control is used.
- 21.5 Water pump must be stock type in stock location.
- 21.6 No electric water pumps.
- 21.7 *NO ANTI - FREEZE ALLOWED AT ANYTIME.*
- 22. CLUTCH, PRESSURE PLATE AND FLYWHEEL**
- 22.1 Clutch and pressure plate must be OEM stock and unaltered with full stock fiber disk for that make and model.
- 22.2 No button clutches.
- 22.3 OEM Steel flywheel for that make and model with no modifications. Minimum weight 16.0 pounds weighed on Rockford Speedway Scale.
- 22.6 Two (.75 min.) inspection access holes must be provided in bell housing or scatter shield, side by side, front to rear, visible from the top, so both pressure plate and flywheel are visible.
- 22.7 Clutch explosion protection required.
- 23. TRANSMISSION / TRANSAXLE**
- 23.1 Stock manual or automatic for corporate make.
- 23.2 Absolutely *NO* deviation from stock.

23.3 No shift kits allowed.

#### **24. DIFFERENTIAL**

24.1 Differential housing must be stock for that make, model and manufacturer, and be unaltered.

24.2 No special order, high performance or non-OEM rear end housings.

24.3 Locked differential only. Must be locked by either welding or mini-spool only.

24.4 Gear ratio: 6.59:1. This is a maximum final drive ratio, measured with transmission in any gear.

#### **25. DRIVELINE**

25.1 Two drive wheels only. Front or rear.

25.2 One piece drive shafts for rear drive cars, minimum outside diameter 2.5".

25.3 All drive shafts must be steel and stock length.

25.4 Driveshafts *must* be painted white.

#### **26. BRAKES AND PEDAL ASSEMBLY**

26.1 Stock rotors, drums and pedals only.

26.2 Master cylinder in stock location and mountings of pedals may be adjusted subject to approval. Cars must have fully functional brakes on all 4 wheels.

26.3 Rear brake must be drum style.

26.4 One hydraulic valve "rear brake adjuster" is allowed but must not be adjustable from driver's seat.

26.5 Approved brake cooling tubes permitted.

#### **27. FRAMES AND UNIBODY**

27.1 Complete bumper-to-bumper steel unibody must be retained.

27.2 The stock steel unaltered floor pan, firewalls, must be retained. NO alterations including, but not limited to, sectioning, channeling or chopping.

27.3 Floor pan may not be cut to lower fuel cell or battery.

27.4 Trunk floor may be removed no farther forward than the rear shock mounts. Trunk floor must be replaced with minimum 22 gage steel. Fuel cell must be center mounted in a complete steel frame and covered. Fuel cell height 10" with driver IN CAR.

27.5 Existing holes in floor, firewalls etc. must be patched with 22 gauge steel. Additional interior panels or "tin kits" not allowed.

27.6 Frames, frame members and suspension must match the wheelbase and model of chassis.

#### **28. ROLL BARS / CAGE**

28.1 Driver assumes responsibility for roll bar installation and workmanship.

28.2 Roll bars must be padded for protection of driver. Recommended is high-density roll bar padding.

28.3 All roll bars must meet NASCAR guidelines as set forth in the NASCAR DWS rulebook and approved for workmanship and design. Round steel 1.5" .090 roll-over bars are compulsory, and must be approved. Aluminum and/or other soft metals not permitted. Roll bars must be welded.

##### ***ROLLCAGE GUIDELINES***

28.4 All cars are required to have rear vertical hoop behind the driver's head connected to left and right front roll bar legs by a roof hoop. The front roll bar legs must follow the contour of the windshield post and cowl. Both left and right front roll bar legs must be equal measurement from centerline of car. Front leg and rear hoop bars from centerline of car must be mounted to body equally on both left and right. Nonconforming cars must get approval of technical director.

28.5 The "A" post must be constructed at a 90 degree angle to the floor board and follow the stock windshield post on both sides.

28.6 The halo must be constructed within two inches of the stock roof. The rear vertical hoop must be supported by a diagonal bar from top left or bottom right to top right to bottom left. The rear vertical hoop must be in line with front and rear roll bar legs. A roll bar, of equal measurement as dash bar, must connect the left and right of the rear vertical hoop at seat height and across the floor pan at the bottom. An additional roll bar must be installed across the bottom of the dash board, extending from the left front roll bar leg to the right front roll bar leg.

28.7 Rear support bars, left and right, must extend from the top of the rear vertical hoop to the rear of the frame in the trunk compartment. A rear loop bar must be extended from rear support bars across the rear of the trunk

- area and must be welded to trunk floor at rear panel. The front leg bars and rear vertical hoop must be connected with a minimum of three horizontal door bars, excluding floor bar, on both left and right sides.
- 28.8 The door bars must be spaced equally from top to bottom as space permits. Left door bars must have four vertical studs equally spaced. Two angular studs must be attached from the bottom door bar to frame rail.
  - 28.9 Butt welds, joints and connections are recommended to include gusset for reinforcement.
  - 28.10 Main roll cage construction MUST remain within the "Driver Area" and may not protrude into or outside firewall except: A maximum of four round 1.75" maximum diameter reinforcement tubes may pass through the front firewall. Two (2) must attached beyond the front wheels. The two remaining tubes must attach behind the centerline of the front wheels. Non-strut cars may use one vertical bar per side at center of wheel.
  - 28.11 A maximum of 4 reinforcement tubes may extend from the main roll cage hoop rearward. They may pass through the rear fire wall and extend into trunk area and must attach beyond rear wheels and tires. Two of the four must attach to the top of the roll cage hoop. Attachment points may NEVER dissect, bisect or enter into any part of stock unaltered floor pan or pass through any firewall. Rear roll over may dissect the floor pan.
  - 28.12 One bent tube may attach to the driver side "A" post and extend forward as a "Mark Martin" bar.
  - 28.13 Protection of radiator is optional, provided all "bars" remain in front of front wheels and do NOT breach, dissect or enter into any part of the stock unibody construction.
  - 28.14 Protection of fuel tank is optional, provided all "bars" remain behind rear wheels and tires and do NOT breach any part of stock floor pan or connect to wedge adjusters.
  - 28.15 All cars must have a horizontal bar connecting front halo with rear hoop at centerline of car.
  - 28.16 A windshield bar connected from dash bar to roof halo must be installed.
  - 28.17 Driver's seat must be fastened securely and no part of the seat may be rearward of any part of stock front door opening. Drivers' seat must be located 14 inches minimum from center of seat to closest door bar. Driver side "deflector plates" must be attached to the door bars.
  - 28.18 Measurement of cage, both left and right, should be equal from centerline of car.

## **29 SUSPENSION**

- 29.1 Steel springs that are stock appearing may be used; however, they must fit in stock mounts and location. One spring per wheel assembly.
- 29.2 Wedge bolts allowed.
- 29.3 Spring buckets may not protrude through stock floor pan.
- 29.4 Suspension parts must remain stock as provided for that make and model on both sides of vehicle, except upper A-frames or strut mounts may be altered from stock to adjust camber and caster but not to exceed 6 degrees positive or negative with driver out of car, non-adjustable rear control arms with stock dimensions and stock dimension bushings allowed. Hood may not be altered in any way due to alteration of upper strut mounts. No altering to lower A-frames and strut mounts. No sectioning, channeling, altering, plating or chopping allowed. No ball joint spacers. Bushings must be made of pliable material. No heim joints or monoballs allowed.
- 29.5 Strut or shock price must not exceed \$100 net, available at all normal retail outlets.
- 29.6 Any non-adjustable type shock that fits in stock mounts in stock position allowed. No coil over shocks.
- 29.7 On non-strut cars, front upper shock mount may be raised. The extended mount may not exceed 3 inches in height and must remain "on center" and "in line" with original mounts.
- 29.8 Single piece stock appearing sway bars only. May be adjustable. One bar per car.
- 29.9 A plate may be added to bottom of left lower control arm.
- 29.10 On leaf spring assemblies, lowering blocks are acceptable provided they do not alter or replace stock mountings.

## **30 SPINDLES AND HUB**

- 30.1 Stock spindles and hubs only, must be same type on both sides and stock for that model and make with no alterations. No cutting, chopping, lightening.
- 30.2 Front wheel drive cars may run approved replacement aluminum hubs on rear only.

## **31. STEERING**

- 31.1 Steering must be stock. Approved heim joint tie-rod ends allowed.
- 31.2 Stock power steering allowed. All components must be stock for make and model.
- 31.3 Steering "Ratio Multiplier" units not allowed.
- 31.4 Finger / Hand protection is recommended.

31.5 Quick release steering wheel system, designed and approved for that use, is required. Steering wheel nose guard or center pad required.

31.6 One piece steering shafts not allowed.

**32. GROUND CLEARANCE**

32.1 Minimum ride height 4 inches with driver in the car, except exhaust.

32.2 Dragging exhaust systems will result in disqualification

**33. WHEELS**

33.1 Steel wheel, 7" X 13" diameter only.

33.2 No spacers allowed.

33.3 Black wheels must be painted a bright color on backside.

33.4 Bleeder valves are not allowed.

**34. TIRES**

34.1 Only approved tires, available from Forest City Tire Sales, are allowed for competition.

34.2 No devices or material for disseminating softening materials or compounds changing composition or character of tire allowed any time. Failure to comply will result in disqualification, loss of season to date points and suspension.

34.3 Rockford Speedway Tire Rule is in effect for this division

**35. WEIGHT**

**ALL WEIGHTS INCLUDE DRIVER**

35.1 2,450 lbs. base weight.

35.2 Deduct 100 pounds for 2,000 cc. or less engine displacement.

35.3 **Right side weight shall be at least forty-four (44%) percent and front axle shall be at least fifty-two (52%) percent of the total weight with the driver in the car and in position.**

35.4 *Management reserves the right to alter, change or adjust weight limits at their option and add additional weight to non-conforming cars.*

**36. GAS TANK INSTALLATION - SECTION 7**

**37. PERSONAL PROTECTION REQUIREMENTS - SECTION 7**

**38. ELIGIBILITY - SECTION 7**

**39. GENERAL POLICY – SECTIONS 1- 7**

**40. NUMBER / APPEARANCE - SECTION 7**

**41. TYPES OF RACING EVENTS - SECTION 3**

**42. CLAIM RULES - CLAIM RULE DOES NOT APPLY.**

**'Internationals' International division cars will be allowed to compete with this division on a trial basis. Car must be built to exact 2012 Jefferson Speedway International rule specifications in the spirit of said rules and compete on the specified tire stated in those rules or race tire allowed by Rockford Speedway. Approved safety hub allowed on rear. International weights will be as follows:**

Actual displacement in cubic centimeters.....	Minimum weight
0 to 1749.....	2300 lb.
1750 to 2049.....	2350 lb.
2050 to 2299.....	2400 lb.
2300 to 2600.....	2450 lb.

**All Cars: Minimum front-end weight must be 57%. Minimum right-side weight must be 45% of total.**

**This is an experimental basis and management may adjust weight, tires, etc on any car or cars in the interest of level competition.**

# NASCAR

## ALL-AMERICAN SPORTSMAN

This Rockford Speedway Division will compete under the sanctions of NASCAR. The specifications listed will become part of the official NASCAR Rule Book, except in cases of obvious conflict. All technical rules will generally fall within NASCAR and R.A.C.E. Specifications. Any disputes will be resolved by NASCAR officials. All drivers in this division must be members of NASCAR and R.A.C.E. to compete.

### NOTICE

All equipment is subject to the approval of NASCAR officials. No equipment will be considered as having been approved by reason of having passed through inspection unobserved. Any equipment which does not conform to specifications, intent or tolerances contained in this NASCAR rulebook, will not be eligible for approval.

**NOTICE:** Consult Section 7 of this book for minimum specifications that apply to divisions.

### **1 WHEEL BASES AND ELIGIBLE MODELS**

- 1.1 Any 1960 or newer American-made non-convertible passenger car with wheelbase over 108-inches (Ford and Chrysler over 104-inches).
- 1.2 Wheelbase must be within 1-inch of stock. Maximum tread width 63-inches, measured center to center of tires at spindle height (front and rear).

### **2 BODY AND APPEARANCE**

- 2.1 All cars must remain stock appearing with complete fenders, quarter panels, doors, roof, hood and trunk lid.
- 2.2 Stock steel roof with A, B, & C posts required. Fivestar fiberglass metric Monte Carlo roof allowed in stock location with stock configurations, no cutting of posts.
- 2.3 Front wheel drive and truck body styles must be pre-approved by management (Lumina-Taurus-Avenger, etc).
- 2.4 Stock steel or professionally built aluminum bodies required.
- 2.5 Bodies cannot be shortened, chopped or channeled, light moldings and stock appearing metal grill required. All doors must be welded shut.
- 2.6 Stock hood with reinforcements removed or fiberglass hood required. Hood latch must be removed.
- 2.7 No multi-plane spoilers. Maximum spoiler length 5". Maximum spoiler width 60". Spoiler may not extend outside body by more than 1-inch. No wings or skirts allowed.
- 2.8 No air scoops or holes in hood allowed. Filler panels painted with reflective colors required.
- 2.9 Front and rear bumpers must appear stock. Bumper ends must be capped or connect to body. Sunroofs must be closed in with Lexan or Metal.
- 2.10 Body must be within 2" from outside of tires.
- 2.11 Tow hooks on front and rear required. .25" cable has proved inadequate.

### **3 WINDSHIELDS AND GLASS**

- 3.1 Stock or Lexan windshields required, all other windows (if used) must be of Lexan.

### **4 ENGINE LOCATION**

- 4.1 Chevy engines must be located so that the furthest forward spark plug is in line with or ahead of the upper ball joint's centerline. All other engines allowed a 2-inch set back. Minimum crankshaft centerline height 10.5" (front and back). Maximum offset (right-left) 3".

### **5 ORIGIN**

- 5.1 Engine must be of same manufacturer as chassis and body.

### **6. ENGINE DISPLACEMENT**

6.1 Maximum displacement 362cid (Chrysler products 368cid).

## **7. ENGINE BLOCK**

7.1 No aluminum blocks

7.2 A minimum of zero deck height required.

## **8. ENGINE PISTONS / RODS**

8.1 Flat top pistons required.

8.2 Magnetic steel connecting rods only. Honda journal rods not permitted.

## **9. OIL PANS/OIL SYSTEMS**

9.1 A 3/4"NPT inspection hole in oil pan required. Inspection hole must be located in line with second or third rod journal of crankshaft, on either side of pan and above sump area (oil level). Hole in windage tray in line with inspection hole required.

## **10. CRANKSHAFT**

10.1 Production type steel crankshaft with normal configuration counter weights required.

## **11. CYLINDER HEADS**

11.1 Stock or stock replacement cast iron unaltered heads (no porting, polishing, acid dipping, or gasket matching allowed) required. No aluminum heads allowed.

11.2 The only stock replacement heads allowed are World Products SR I052 #4266B and #4267B.

11.3 Minimum combustion chamber 62cc, maximum 2.02-inch intake and 1.6-inch exhaust valves required.

11.4 Maximum of two valves per cylinder.

11.5 No Bowtie, Vortec or 18-degree heads allowed on GM products.

11.6 Valve spring retainers are the only titanium parts allowed.

## **12. INTAKE MANIFOLD**

12.1 Completely stock passenger car 2-bbl. cast iron intake and exhaust manifolds required.

12.2 (Edelbrock Performer #2101 or Edelbrock Performer RPM #7101 allowed with 25# penalty)

12.3 No grinding, polishing or altering allowed.

12.4 No Bow-Tie manifolds.

12.5 Internal heat riser crossover must remain in place.

## **13. CAMSHAFT / VALVE LIFTERS AND ROCKER ARMS**

13.1 Hydraulic cam/lifters only.

13.2 Maximum lift at valve: GM-.490 inch, Ford/Mopar-.520 inch.

13.3 Roller tip rocker arms allowed, but must retain original pivot type (ball & socket).

13.4 No solid lifter or roller cams allowed.

## **14. COMPRESSION**

14.1 Maximum 10.8 to one compression ratio.

## **15. EXHAUST**

15.1 Center dump and log style manifolds allowed.

15.2 Max exhaust manifold inside diameter 2-inches.

15.3 No cast iron header style exhaust manifolds allowed.

15.4 Maximum diameter 2 1/2" before collector and/or muffler, 4 1/2" maximum diameter behind muffler.

15.5 Exhaust must exit beneath car and behind driver, pointing downward. Effective mufflers required.

## **16. CARBURETOR**

16.1 Stock unaltered 500 CFM Stock Holley 4412 2 bbl. or 1.375" Rochester allowed on all cars.

16.2 No alterations except removal of choke "Butterfly" allowed.

16.3 Double return springs required.

16.4 Holley 4412/650 cfm carburetor #80541-1

16.5 Carburetor Rework Guidelines:

A. Body of Carbs:

1. No polishing, grinding, or drilling of holes allowed.

2. Gasket surfaces may be machined for improved sealing.

B. The choke may be removed, but all screw holes must be permanently sealed.

C. Choke horn may not be removed.

- D. Boosters may not be changed. Height, size, and shape must remain standard and unaltered.
- E. Venturi area must not be altered in any manner. Casting ring must not be removed.
- F. Base plate must not be altered in shape or size.
- G. Butterflies: Stock butterflies must not be thinned or tapered. Idle holes may be drilled in butterflies. Screw ends may be cut even with shafts, but screw heads must remain standard.
- H. Throttle Shafts: Shafts must remain standard and must not be thinned or cut in any manner.
- I. Any attempt to pull outside air other than straight down through the venture is not permitted.
- J. Jets may be changed. No dial-a-jet devices.
- K. No addition of any material, such as epoxy, may be added to carb or parts except to seal vacated external screw holes.

**17. CARB SPACERS, GASKETS, MOUNTING**

- 17.1 Carb Adaptor: 1.5" max thick w/gaskets. Bores must be straight (not tapered, angled beveled or grooved). Original orientation required. No part of adaptor may protrude into plenum of Intake Manifold. Adaptors are one piece only.
- 17.2 No adapter allowed on CCMP.

**18. AIR INTAKE**

- 18.1 Air cleaner required to act as flame arrestor. No air induction boxes, **x-stream top plate** or ram air units.

**19. FUEL SYSTEMS**

- 19.1 OEM type, mechanical fuel pump, in original location, required.
- 19.2 Steel fuel lines located outside driver's compartment required.
- 19.3 Remote fuel filter allowed.

**CCMP**  
**CONCEPT CRATE MOTOR PROGRAM**

Approved CCMP models are:

GM 602 CCMP motor will be allowed one Holley 4 bbl 650 cfm carburetor #80541-1 with no adapter plate or spacer. Weight may be adjusted for fair competition. The CCMP will use the Holley 4 bbl. 650 cfm carburetor with GM Stock 15.5lbs. flywheel and 1.625" headers. Maximum cost of headers is not to exceed \$225.00. No stepped, 180 degree or Tri-Y headers.

Base Weight: 3,100 pounds.

All crate engines may not be altered from factory specs. Any evidence of tampering with engine components will result in disqualification, confiscation, fine, and suspension for balance of season.

Tech staff reserves the right to impound motors for inspection or dyno testing.

Factory Seals may be removed for tech purposes, those engines will not be required to be recertified, allowing for more in-depth technical inspection throughout the season.

**No refreshing, buy new instead. Repairs allowed with prior management approval.**

**20. ELECTRICAL**

- 20.1 Stock type (HEI) ignition components only. Any coil permitted. Firing order may not be altered. No MSD boxes or dual-point distributors. Batteries must be securely mounted ahead of rear axle and away from fuel container and lines. All batteries in driving compartment must be in an approved sealed battery box. Maximum 12 volt system.

**21. COOLING SYSTEM**

- 21.1 Any metal radiator that does not alter the exterior appearance of car allowed. Fan protection (20 gauge minimum thickness) required. Overflow tank located under hood required.
- 21.2 **NO ANTI - FREEZE ALLOWED AT ANYTIME.**

**22. CLUTCH, PRESSURE PLATE AND FLYWHEEL**

- 22.1 Manual transmissions must utilize stock all steel type pressure plate and steel or cast iron flywheel (min 15.5 lbs.). Clutch disc must be minimum of 10" diameter with stock full fiber disc.

**23. TRANSMISSION / TRANSAXLE**

- 23.1 Stock automatic transmission with operating 11-inch minimum diameter torque converter.
- 23.2 Torque converter post-race inspection will occasionally be required.
  - Option 1; install drain plug in torque converter.
  - Option 2; remove torque converter for detailed inspection.
- .3 All forward and reverse gears must operate.
- .4 Transmission overflow bottle required. No rubber transmission lines.
- .5 Transmission cooler not allowed in driver compartment.
- .6 A manual stock OEM transmission will be permitted.
- .7 All gears must be operable.
- .8 No 5-speed transmissions.
- .9 No straight cut gears or gun-drilled main shafts, no lightening of gears on main shaft.

#### **24. DIFFERENTIAL**

- 24.1 Rear end must be stock for that make car.
- 24.2 Ford 9" allowed, unlocked or locked by welding or spool only.
- 24.3 If using 9" ford rear-end, upper control arm mounts on frame may be raised max. 1".

#### **25. DRIVELINE**

- 25.1 Minimum diameter 2.5" steel driveshaft required.
- 25.2 Driveshaft must be painted a bright reflective color.
- 25.3 Safety hoop required on front half of driveshaft. Driver must be protected from driveshaft entering into driving compartment.

#### **26. BRAKES AND PEDAL ASSEMBLY**

- 26.1 Stock brake units only.
- 26.2 Four-wheel brakes required at all times.
- 26.3 Master cylinder and pedals must remain in stock location.
- 26.4 No "made for racing" components allowed.
- 26.5 Drilled rotors not allowed (except stock replacement).
- 26.6 **One brake proportioning valve allowed.**
- 26.7 Rear drum brakes required.

#### **27. FRAMES AND UNIBODY**

- 27.1 GM chassis must retain original wheelbase. Ford/Chrysler may use GM Metric frame.
- 27.2 Complete stock steel frame or unit-body must be retained to a point 6" behind center of rear axle. Replacement with square tubing allowed rear of that point.
- 27.3 Front stub and rest of frame must match.
- 27.4 Steel firewall and floorpan required.
- 27.5 Passenger side interior can be tinned over from top of driveshaft tunnel to passenger side door bars.
- 27.6 Minimum frame height 4.75".

**MID SIZE GM METRIC CHASSIS**-Lower right A-frame may be 1" longer than stock. Coleman steel hubs or full size GM spindles allowed. Steering center link modifications (to improve bump-steer) allowed. Any stock production rear end allowed, provided that lower control arm/shock mount locations remain in the stock position for the metric chassis. Rear end may not exceed 58 inches in width from axle flange to axle flange. Aftermarket or S-10 axle required on right side of metric rear ends.

#### **28. ROLL BARS / CAGE**

- 28.1 Driver assumes responsibility for roll bar installation and workmanship.
- 28.2 Roll bars must be padded for protection of driver. Recommended is high-density roll bar padding.
- 28.3 All cars must have a well constructed, properly welded and gusseted 4 or 6 point roll cage made of minimum 1.75" .090 wall tubing or equivalent.
- 28.4 Roll cage must have four uprights properly welded to frame.
- 28.5 Right side of roll cage may not be located inboard more than right rails of front and rear stubs.

- 28.6 Main roll hoop must be behind driver and be reinforced with a full x-bar configuration. Cage must be reinforced from left to right with bars under the dash, along floorboards, and behind driver in main roll hoop.
- 28.7 At least two bars must extend from main roll cage rearward to frame kick-up or beyond. A minimum of four equally spaced horizontal bars required in driver's door, three in passenger side door.
- 28.8 Door bars must be connected with a minimum of two equally spaced vertical studs. Two angular bars must connect bottom door bar to frame rail.
- 28.9 All welds in cage and door structure must be gusseted.
- 28.10 Driver's foot protection bar required. Left side door bar deflector plates of at least .125" steel required.
- 28.11 Front hoop must connect to front roll cage uprights.
- 28.12 Uni-body roll cage construction: contact competition director for guidelines.

## **29 SUSPENSION**

- 29.1 Any stock appearing steel spring that fits in original mount in original position allowed.
- 29.2 One steel non-adjustable, nonrebuildable shock, with a welded bearing, with a maximum MSRP \$80, per wheel. No heim joint shocks allowed.
- 29.3 Screw Jacks, spring adjusters, adjustable spring spacer units where shock mounts through spring (front), screw type (wedge bolt) where shock mounts outside spring (rear) allowed.
- 29.4 Spring buckets may protrude through floor pan.
- 29.5 All other components must remain stock and in stock location, except where otherwise stated.
- 29.6 Lower A-frames may have bushings replaced with steel insert type.
- 29.7 Rear Control link rubber bushings may be replaced with **approved** non-metallic **unaltered** stock replacement parts.
- 29.8 Tubular upper A-frames allowed, may relocate upper frame mount.
- 29.9 No monoball, heim joints or clevis' permitted on suspension components.
- 29.10 Stock front, solid (non-tubular) passenger car stabilizer bar in stock position allowed.
- 29.11 Frame mounted stabilizer adjusters allowed.
- 29.12 1" shock extenders in front and 2" in rear allowed.
- 29.13 No lift bars, rear sway bar or traction devices.
- 29.14 Non-adjustable rear control arms with stock dimensions and **approved unaltered** stock style bushings allowed.

## **30 SPINDLES AND HUB**

- 30.1 Stock unaltered spindles, hubs, and steering components required.
- 30.2 Coleman steel hubs allowed.
- 30.3 No lowered spindles.
- 30.4 Heim joints allowed on outer tie rod ends.

## **31. STEERING**

- 31.1 Fabricated steering column must incorporate 2 U-joints.

## **32. GROUND CLEARANCE**

- 32.1 Minimum ground clearance 4.75" with driver in car, at any point including spoilers, scoops, and mufflers, except front crossmember, which is 2.75".

## **33. WHEELS**

- 33.1 Minimum wheel weight of 19.0 lb. - IMCA "sticker" legal.
- 33.2 Acceptable only are steel wheels with a maximum inside width of 8" measured bead to bead.
- 33.3 Black wheels **MUST BE** painted white, silver or yellow on complete backside.
- 33.4 Bleeder valves are not allowed.

## **34. TIRES**

- 34.1 Only approved tires, available from Forest City Tire Sales, are allowed for competition.
- 34.2 No devices or material for disseminating softening materials or compounds changing composition or character of tire allowed any time. Failure to comply will result in disqualification, loss of season to date points and suspension.
- 34.3 Rockford Speedway Tire Rule is in effect for this division
- 34.4 Undocumented, unauthorized or unmarked tires will result in immediate disqualification, loss of all points and purse earned and a minimum two-week suspension from competition.

## **35. WEIGHT**

### **ALL WEIGHTS INCLUDE DRIVER**

- .1 Minimum total weight is 3100 lbs.
- .2 add **25** lbs. if body and chassis don't match.
- 35.3 IMCA Northern SportMod built to exact IMCA Northern SportMod rules in the spirit of said rules, will be permitted on a trial basis at 2900 lbs 52% front and 44% right side weight.
- 35.4 52% front axle, and 42% right side.
- 35.5 All weights must be properly anchored to frame rail outside driver's compartment. Weights must not be lower than bottom of frame rail.
- 35.6 Ballast must be painted white and lettered with car number.
- 35.7 Management reserves the right to alter, change or adjust weight limits at their option and add additional weight to non-conforming cars.

### **36. GAS TANK INSTALLATION - SECTION 7**

### **37. PERSONAL PROTECTION REQUIREMENTS - SECTION 7**

### **38. ELIGIBILITY - SECTION 7**

### **39. GENERAL POLICY – SECTIONS 1- 7**

### **40. NUMBER / APPEARANCE - SECTION 7**

### **41. TYPES OF RACING EVENTS - SECTION 3**

### **42. CLAIM RULES - CLAIM RULE DOES NOT APPLY.**

**FORD AND CHRYSLER EXCEPTIONS**--Ford and Chrysler will be permitted some variation to improved competitiveness. Such variation requires prior approval by director of competition.

**FRONT WHEEL DRIVE EXCEPTION**--A front wheel drive platform will be permitted some variation to improve competitiveness. Such variation requires prior approval by director of competition.

**IMCA Northern SportMod**- The IMCA Northern SportMod will be allowed to compete with this division on a trial basis. Car must be built to exact IMCA Northern SportMod specifications in the spirit of said rules and compete on the specified tire and weight stated in this rulebook. Modifieds must run a legal 500cfm 2bbl. This is an experimental basis and management may adjust weight, tires, etc on any car or cars in the interest of level competition.

# NASCAR

## Late Models

This Rockford Speedway Division will compete under the sanctions of NASCAR. The specifications listed will become part of the official NASCAR rulebook, except in cases of obvious conflict. All technical rules will generally fall within NASCAR and R.A.C.E. specifications. NASCAR officials will resolve any disputes. All drivers in this division must be members of NASCAR and R.A.C.E. to compete.

**NOTICE:** All equipment is subject to the approval of NASCAR officials. No equipment will be considered as having been approved by reason of having passed through inspection unobserved. Any equipment which does not conform to specifications or tolerances contained in this rulebook, will not be eligible for approval.

### **BIG 8 SERIES CARS LEGAL**

**CONSULT SECTION 7 FOR MINIMUM SPECIFICATIONS THAT APPLY TO ALL RACING DIVISIONS**

#### **WHEELBASE & TREAD WIDTH**

Minimum wheelbase 104", *plus/minus 1 inch*

Maximum tread width 65", measured center to center of tires at spindle height (front and rear).

#### **CHASSIS**

Tube or stock stub allowed. Frame rails must be a minimum of 2-inch by 3-inch .125 wall tubing.

Minimum ground clearance 3.5" with driver!

#### **ROLL CAGE**

All roll cage tubing must be at least 1.75" x .090" wall. Welded gussets required on all joints. At least four evenly spaced horizontal bars required on left, and three on right side. X-configuration on right side, counts as one bar.

All door bars must be mounted to the frame rails and the main roll cage uprights.

Door bars must be connected with a minimum of two equally spaced vertical tubes.

Left side door bar deflector plates of at least .125" steel required. Diagonal bar in top hoop required.

Floor pan under driver must be heavy-gauge steel.

#### **SUSPENSION**

Conventionally mounted 5-inch springs or coil over type suspensions.

Approved Non-Adjustable Shocks series; Afco 13T, R, S, 21, ARS 2000, Bilstein SZ, SN, Carrera 65,67, Genesis GSO, Integra 431, Pro A, AC, TA, PG, QA1 21, 50, **62, 67**. Manufacturers components must be used, valving optional.

Post Race shock disassembly is the responsibility of the Car Owner/Crew Chief. Bring Tools or make arrangements.

NO Bump-Stops/Rubbers, Compression-limiting or Coil-Bind set-ups.

One shock/spring per wheel. One (1) conventional (single coil), spring rubber per spring allowed.

Rear suspension must be solidly mounted (no rubber bushings). Heim Joints only.

**No Coilover eliminators or sliders allowed.**

No lift bar, fifth coil or other spring-loaded/hydraulic suspension device allowed. No rear stabilizer bars.

#### **SPINDLES & HUBS**

Any steel spindle allowed. Aluminum steering-arm and ball-joint mounts allowed. Aftermarket hubs with 5/8" wheel studs required, **maximum retail price \$325**. No gun-drilled studs permitted.

Wide five hubs and spindles allowed with no weight penalty.

#### **STEERING**

Rack & Pinion, or steering box with center link style required. No electric power steering units.

Quick release steering wheel hub required.

Collapsible steering shaft recommended.

#### **REAR END**

Stock or rear spur gear type quick change units with steel tubes, No mini type quick change. Maximum camber ½ degree.

Spool, Detroit Locker (ratchet type), and Torque Sensing, differentials are permitted.

One-piece straight spline drive plates only. Drain plugs must be safety wired.

**Magnetic steel axles only, blue drilled axles allowed.**

#### **BRAKES**

Four wheel brakes required at all times.

Single or dual piston (steel or aluminum) calipers.

Four (4) piston calipers allowed with 30 lb weight penalty. Maximum retail price \$190.

Rigid mounted rotors, maximum diameter 12¼" rotors, no drilling permitted.

No floating calipers or rotors, no self centering rotors, ABS units or brake recirculation systems.

Only one brake bias adjusting unit per car.

#### **ENGINE LOCATION**

GM engines must be located so that the center of the furthest forward spark plug hole is no more than 2" behind the front axle centerline.

Ford and Chrysler allowed 4" engine set back. **302 Ford allowed 4" engine set back with 30 lbs penalty, otherwise 2" set back.** *Ford/Mopar based engines may have weight adjusted in the spirit of competition.*

Crankshaft centerline 10" minimum ground clearance.

#### **ENGINES**

**Limited Concept Engine** –Two valves per cylinder. No aluminum blocks or heads. GM & Ford - 362 CID maximum, Chrysler - 373 CID maximum. All engines must meet the following specifications regardless of manufacturer: Stock or stock replacement cast iron unaltered heads with factory valve angles (no angle milling, porting, polishing, acid dipping allowed). GM Bowtie numbers 14011058, 10134392, (casting number 14011034 and 12480034), World Products Sportsman II numbers 011150, 011250 allowed. Ford 351N and 352N heads, World Products Windsor Sr. 053040 allowed. Chrysler 5249769, 4529446, **L-AX** heads. Casting numbers must be visible on all heads. Gasket matching not permitted. Minimum combustion chamber 62cc, maximum 2.02-inch intake and 1.6-inch exhaust valves required. Flat top pistons required. A minimum of zero deck height required. 10.8 to one maximum compression ratio. Connecting rods must be magnetic steel. *Rod journal minimum diameter 1.900". Oil pan minimum depth 6.5".* A 3/4" NPT inspection hole in oil pan required. Inspection hole must be located in line with second or third rod journal of crankshaft, on either side of pan and above sump area (oil level). Hole in windage tray in line with inspection hole required. Valve spring retainers are the only titanium parts allowed. No radius edge lifters. Lifters must be able to rotate in their bores. No roller or mushroom cam/lifters. Maximum valve lift - .600" (measured at retainer). OEM style rocker arm mounting required. Firing order may not be altered. Ignition system may not be computerized, programmable or have memory circuits. No magnetos, crank trigger, multiple coil or programmable ignition systems allowed. Production type steel crankshaft with normal configuration counter weights. No dry-sump or vacuum systems of any kind allowed. External single stage oil pump allowed on Ford engines. OEM type, mechanical fuel pump, in original location, required. Chrysler engines add 20 lbs. for CID over 362.

Intake Manifold: Edelbrock Victor Jr. 2975 (GM), 2915, 2920 (Chrysler), 2921, 2980, 2981 (Ford). Plenum and port configuration must remain as-produced. No porting modifications, including gasket matching. No spacer/Adaptor plates to head. If Bee-Hive valve springs are used, the competitor will be required to switch to conventional style valve springs for post race tech purposes.

**GM Crate Engine** Part number 88958604, must be used as produced. Maximum 2" set back. Ignition: MSD with Rev-control required (6600 RPM). Mounting on right side of dash required. Carburetor: Holley 650-HP P/N 80541-1 required. No modifications allowed. All crate engines may not be altered from factory specs. Any evidence of tampering with engine components will result in disqualification, confiscation, fine, and suspension for balance of season. Factory/Certification Seals may be removed by Officials for tech purposes, allowing for more in-depth technical inspection throughout the season. Tech staff reserves the right to impound motors for inspection or dyno

testing. GM Crate engines with any or all of the **following** updates will weigh 2825 lbs. Specific updates are; 1.6 rocker arms, Small Harmonic Balancer, Carb Spacer **Maximum compression can never be greater than 9.6:1**

**Carburetor:** Holley 4412-2 bbl. Holley 4412 Carburetor Rework Guidelines:

Body of Carbs: No polishing, coating, grinding, or drilling of holes allowed. Gasket surfaces may be machined for improved

sealing. The choke may be removed, but all screw holes must be permanently sealed. Choke horn may not be removed.

Boosters may not be changed including no additional holes. Height, size, and shape must remain standard and unaltered.

Venturi area must not be altered. Casting ring must not be removed. Base plate must not be altered in shape or size.

Butterflies: Must not be thinned or tapered. Screw ends may be cut even with shafts, but screw heads must remain standard.

Throttle Shafts: Shafts must remain standard and must not be thinned or cut in any manner. Metering block may be plugged, no additional holes allowed, must remain stock appearing for carb style, no aftermarket blocks permitted.

Any attempt to pull outside air other than straight down through the venture is not permitted.

Jets may be changed. No dial-a-jet devices.

No addition of any material, such as epoxy, may be added to carb or parts except to seal vacated external screw holes.

Epoxy allowed on boosters of 4412-2 bbl. at main body only.

Carb Adaptor: 1.5" max thick w/gaskets. Bores must be straight (not tapered, angled beveled or grooved). Original orientation required. No part of adaptor may protrude into plenum of Intake Manifold. Adaptors are one piece only.

#### **RETURN SPRINGS & AIR CLEANER**

Double return springs required

Air boxes allowed with cowl inlet only.

#### **EXHAUST**

Headers allowed on all engines (max retail price \$650). Tri-Y not allowed, no Merge-Collectors.

Exhaust must exit behind driver. Under car allowed 100-decibel max. **Right door exit must be 12 " max from ground, not point up, and be 95-decibels max.** NO custom, one of a kind or homemade headers.

#### **CLUTCH, TRANSMISSION & DRIVESHAFT**

Stock transmission with operating reverse gear required. No straight cut gears. Counter gear must be driven by input shaft.

Made-for-racing clutch required. Two disk 5 ½" minimum. Carbon clutch not permitted.

Steel or Aluminum driveshaft minimum diameter 2½". Safety hoop required on front half of driveshaft.

Driveshaft must be painted a bright reflective color.

#### **RADIATOR/COOLING**

Metal radiator mounted in front of engine, between frame horns.

Fan protection and overflow tank located in engine compartment required.

Water pump must be stock type in stock location.

Antifreeze is not allowed.

#### **FUEL & FUEL CELL**

Fuel cell complete with 1/8" steel can, interior bladder, foam baffle and rollover valve required. No deflector plates.

Fuel cell must be mounted behind rear axle, between frame rails.

Over-Tail chassis – maximum 15 gallon capacity (25"x18"x10") and must have ASA bar.

Bottom of fuel cell must be at least 10 inches from the ground.

Filler must be accessed through deck lid. Filler spout may be extended, but not connected to bodywork.

All vents must be valved to eliminate leakage.

Aeroquip or equivalent gas line required. Routing must be outside of cockpit and protected from damage.

**Fuel must meet properties of track supplied fuel.**

#### **BODY & APPEARANCE**

Five Star, ARP or equivalent template short track late model body only, **subject to tech inspector scrutiny**

Minimum roof height 47".

Spoiler: Single plane, 5"(measured from deck plane) x 60"(measured across rear) max.

Deck height 34.5" max.

Minimum ground clearance including nose and rocker panel is 4".

All windows must be of Lexan. 12" max vent (wing) window.

No venting cockpit air allowed. 2 – 3" maximum diameter hoses and ducts allowed for driver cooling.

Weight penalties may be assessed for bodies not conforming to Five Star guidelines, dimensions, and/or templates.

#### **WEIGHT**

Limited Concept Engine – 2850 lbs. Chrysler over 362 – 2870 lbs.

GM Crate Engine with RPM Rev-control – 2775 lbs.

GM Crate Engine with updates and RPM Rev-control – 2825 lbs.

LaCrosse 9 to 1 iron intake & exhaust, conventional springs, GM brakes – 2825 lbs. (LaCrosse shock rule applies)

Add 30 lbs for four (4) piston brake calipers.

**Add 30 lbs for 302 Ford with 4" engine set back**

**Deduct 50 lbs for certified heads**

Gas allowance for Heats and Features will be listed on the Event Entry Form.

Front axle 49% and right side 42% apply at all times. All weights include driver in seat.

Ballast must be painted white and lettered with car number.

#### **WHEELS & TIRES**

Aftermarket made for racing, steel wheels required. 15" x 8" maximum.

Approved Tires required. See tire rule in Section 7

Chemical treatment of tires (softening) not permitted.

**TOW HOOKS:** Tow hooks on front and rear required.

**BATTERY:** 12-volt systems max. Batteries must be securely mounted ahead of rear axle, away from fuel cell and lines.

Batteries in driving compartment must be in approved sealed battery box. Battery (negative post) disconnect switch recommended.

#### **ELECTRONICS:**

Radio frequencies must be registered with the tech officials.

Video recording from car, limited to 1 track viewing camera only.

Data recording/acquisition not permitted.

# NASCAR RoadRunners

This Rockford Speedway Division will compete under the sanctions of NASCAR. The specifications listed will become part of the official NASCAR Rule Book, except in cases of obvious conflict. All technical rules will generally fall within NASCAR and R.A.C.E. specifications. NASCAR officials will resolve any disputes. All drivers in this division must be members of NASCAR and R.A.C.E. to complete.

## NOTICE

All equipment is subject to the approval of NASCAR officials. No equipment will be considered as having been approved by reason of having passed through inspection unobserved. Any equipment which does not conform to specifications or tolerances contained in this NASCAR rulebook, will not be eligible for approval.

**Gladiator Enduro Series cars meeting exact 2012 Gladiator Enduro V-8 rules allowed to compete up to 3 (three) times per season.**

## **CONSULT SECTION 7 FOR MINIMUM SPECIFICATIONS WHICH APPLY TO ALL RACING DIVISIONS**

### **1. WHEELBASE AND ELIGIBLE MODELS**

- 1.1 Any American made 1948 to 1994 sedan is eligible with wheelbase of not less than 108" for full frame cars. Chryslers and Ford products with wheelbase of not less than 106".
- 1.2 El Caminos, station wagons and miscellaneous body styles allowed with approval of Speedway.
- 1.3 No Camaros, Firebirds, Pintos, T-tops, sunroofs, convertible, jeeps or trucks.

### **2 THE CAR AND BODY**

- 2.1 Complete bumper-to-bumper steel unibody must be retained.
- 2.2 The stock steel unaltered floor pan, firewalls, **trunk and trunk floor construction must be retained.** No sectioning, channeling or chopping allowed. No additional bracing allowed.
- 2.3 Cars must be strictly stock. No cutting, chopping, shortening or cutting allowed. No holes in the hood or roof. Hood must be kept in place at all times. Stock hinges must be used. Front latch must be removed and racing style hood pins must be used. No threaded rod, wire or bolts. Body sheet metal must be kept in place at all times.
- 2.4 Front firewall must be sealed. No holes. Rear seat may serve as firewall.
- 2.5 No lightening of body components: hood, trunk, doors, inner panels, fenders and roof, except clearance for roll bar installation on front doors.
- 2.6 Rear wheelwells must be left in place.
- 2.7 Any sharp protruding objects on cars or in driver's compartment must be removed.
- 2.8 All doors must be welded shut.
- 2.9 Door hinges must remain in place.
- 2.10 A flush, securely mounted exterior driver's door protection plate is permitted. No "rub rails."
- 2.11 Stock seat may be replaced with a "made for racing" seat with approved installation (see section 7-1.11). Stock factory retracting shoulder harness must be replaced with a minimum five (5) point racing belt system
- 2.12 Seat must be mounted in straight-ahead position.
- 2.13 Dash may be removed when a four-point roll cage, with dash bar installed at dash height between the "A" posts of the cage, is installed.
- 2.14 Cars must have complete stock bumpers with welded **1/8" steel** corner plates on both sides attaching to bodywork. **No aftermarket nose pieces or tails allowed.**



- 13.3 Cam lift not to exceed .420 at valve. (Ford / Chrysler cam lift .460)
- 13.4 Stock lifters. Stock push rods. Stock rocker arms.
- 14 COMPRESSION**
- 14.1 Maximum compression ratio allowed is 9.0:1 with no tolerance.
- 15 EXHAUST**
- 15.1 Stock cast iron with no modifications as provided on engine. No center dump styles allowed.
- 15.2 Exhaust must terminate behind driver pointing downward and within 18" of rear end housing. Two (2") pipes allowed. No "H" pipes.
- 15.3 Exhaust must be securely fastened to frame of the car.
- 15.4 Mufflers 100 decibels @ 100 feet minimum.
- 16 CARBURETOR**
- 16.1 Carburetor must be stock OEM street applicable.
- 16.2 Carburetor must be 2 bbl. with Venturi size not to exceed 1 3/16".
- 16.3 Carburetor gaskets may not exceed 1/4".
- 17 CARBURETOR SPACERS**
- 17.1 No spacer plates of any kind.
- 18 AIR INTAKE**
- 18.1 Stock dry paper air cleaner, maximum of 4" tall.
- 19 FUEL SYSTEM**
- 19.1 Stock OEM mechanical fuel pumps only.
- 20 ELECTRICAL / BATTERY**
- 20.1 No dual point distributors.
- 20.2 Stock distributor, stock coil in stock locations.
- 20.3 Batteries must be securely mounted under the hood forward of firewall and covered.
- 21 COOLING SYSTEM**
- 21.1 Stock OEM radiator or aluminum aftermarket radiator (\$150 max) in stock location.
- 21.2 No electric fans.
- 21.3 One-gallon overflow catch-can must be maintained inside engine compartment.
- 21.4 No extra engine coolers.
- 21.5 No antifreeze allowed.
- 22 CLUTCH -- DOES NOT APPLY**
- 23 TRANSMISSIONS**
- 23.1 Stock automatic transmission with at least three (3) working forward gears. 12" Torque converter. Transmission must have all functions including "Park" No extra transmission coolers.
- 23.2 Stock type shifter only.
- 23.3 A single external transmission cooler may be used.
  - (a) Must be mounted under hood, in front of firewall, behind radiator support on right, between wheel well.
  - (b) Maximum cooler size 10"x15.825"
- 23.4 No rubber lines used in transmission cooling. Must be steel.
- 24 DIFFERENTIAL**
- 24.1 Unaltered stock rear end only.
- 24.2 No posi-traction or limited slips.
- 24.3 Only one wheel may drive.
- 25 DRIVELINE**
- 25.1 Must be rear wheel drive. (EIRI)
- 25.2 Driveshaft must be OEM steel and painted white.
- 26 BRAKES**
- 26.1 No deviation from stock allowed.
- 26.2 Brake pedal must remain in stock location and mountings with no extensions or blocks.
- 26.3 Cars must have fully functional unimpeded brakes on all 4 wheels.
- 26.4 Rear drum brakes only. No brake bias devises allowed

26.5 No after-market brakes or components allowed.

## **27 FRAMES**

27.1 Body and frame components must be the same. Must remain in original OEM configuration for that make and model.

27.2 Complete bumper-to-bumper stock frame and unibody must be retained.

27.3 Stub repairs must maintain OEM measurements.

27.4 Rear frames rails may be repaired with 2"x 3"x .120 minimum wall steel tubing, from the back side of the rear wheel hump only. One "cross member" using 1.75" x .090" pipe may be added to attach the frames at the furthest rear point before bumper. Trunk floor must remain intact.

## **28 ROLL BAR INSTALLATION**

28.1 Vehicles, with a wheelbase of 113" or less, must be equipped with a roll bar.

28.2 Driver is responsible for installation, construction and workmanship of roll cage.

28.3 Material used must be 1.75" x .090" or better mild steel. No pipe-fittings, galvanized or exhaust pipe, or conduit allowed. All welding must be electric.

28.4 The roll bar must be located directly behind the driver and reach as close as possible to roof and left side of car. The roll bar must be back braced with a min of 2 bars, from the top of the bar to the rear car frame no further than the rearend (or plate on floor) at an approximate 45-degree angle.

28.5 Roll bar members may attach to either the frame or the floor. For floor installation, attach members to 8"x8" or larger plates which are securely fastened to floor.

28.6 Driver compartment bracing must remain inside the driver's compartment and may not dissect, bisect or pass through either the engine or trunk firewall.

28.7 "Petty" bar may be installed and attached forward to the right "A" post of the cage only.

28.8 Door bars may be used for driver protection only. In some cases, with approval, door bar may extend from front firewall to rear wheel well. Bars may not pass through firewall or wheel well.

28.9 Radiator protection bar consisting (a hoop from top to top of frame rail only) with a 45-degree support on each side allowed.

28.10 A single frame reinforcement bar is allowed on both sides. Bar must be attached to the A post, below the dash bar, dissect firewall and attach to the front frame, behind and at least 8" from the upper A frame.

28.11 Roll bar installation is subject to inspection that will be closely scrutinized. Refer to illustrations for suggested minimum installation.

## **29 SUSPENSION**

29.1 Suspension must work and look stock.

29.2 NO modifying of the suspension or mounting location is allowed.

29.3 Any coil spring that fits in stock location with absolutely no modifications allowed.

29.4 No cut springs allowed-

29.5 No spacers, lumber or chains, etc., may be used to alter stock suspension of that car.

29.6 All four corners of frame must measure within 1 inch of level.

29.7 Front wheel camber angle cannot exceed four (4) degrees, positive or negative.

29.8 No rear sway bars allowed.

29.9 No spring jacks, blocked shocks or reverse shackles permitted.

29.10 OEM style small bodied shocks allowed, must fit stock mounts, \$40 limit per shock. No "made for racing", coil over, overload, cargo ratchet, air assisted or steering stabilizer shocks allowed. No pinching of shocks to stop travel. **PRO Street Stock SS100 Non-Adjustable shock allowed on right front only**

## **30 SPINDLES**

30.1 Stock OEM spindles only for that make and model (metric for metric, etc)

30.2 Oversized studs recommended.

## **31 Steering**

31.1 Stock steering systems only. **Steering column may be replaced with approved collapsible steering shaft, max 32.5" from firewall**

31.2 Quick release steel 'dish" type wheels allowed.

## **32 GROUND CLEARANCE**

32.1 Frame rails must maintain a minimum ground clearance of 6 inches at all times, with driver in car.

## **33 WHEELS**

33.1 Mandatory right side reinforced racing type wheel and studs -- left side racing wheels optional.

33.2 Safety wheel offset: **Minimum 3", maximum 4"**

33.3 No mags, aluminum, or slotted wheels allowed.

33.4 Oversize lug nuts required on all wheels. Studs must protrude through lugs.

33.5 Maximum wheel size: seven (7) inches x sixteen (16) inches.

.6No wheel spacers allowed.

.7Black wheels must be painted white, silver or yellow on back side of wheel completely.

## **34 TIRES**

34.1 Only tire allowed is Forest City Tire Branded radial tire, sold by Forest City Tire Sales.

.2Any loss of a wheel or tire requires driver to immediately leave the race track

.3Undocumented, unauthorized or unmarked tires will result in immediate disqualification, loss of all points and purse earned and a minimum two-week suspension from competition.

## **35 WEIGHT**

35.1 3,500lb minimum all cars.

35.2 Weight determined by Rockford Speedway scale.

35.3 Added weight must be securely mounted to rear frame rail, located between frame rails behind differential.

35.4 Ballast weight must be painted white with car number painted clearly on it.

35.5 No weight allowed in trunk.

## **36 GAS TANK INSTALLATION**

36.1 The stock gas tank must be removed and replaced with a securely mounted 6-gallon outboard marine type tank, plastic or steel.

36.2 Tank must be installed above **rear frame rails**, in center of trunk, as far forward as possible ahead and securely mounted. Tank must fill from inside trunk. No holes in trunk lid. One fuel tank only.

36.3 Fuel tank must be secured by four (4), over the tank (two each direction), 1.5" x .125" straps.

36.4 Fuel cells are optional. Maximum of 12 gallon capacity. No filler tubes. Vent tube must exit outside car.

36.5 The fuel line must exit from the top or side of the tank. No fuel lines in the driver's compartment.

36.6 Fuel tank rupture or fuel spillage will draw an immediate black flag.

## **37 PERSONAL PROTECTION REQUIREMENTS**

37.1 Driver must wear full racing firesuit. No polyester clothing allowed.

37.2 Five point 3-inch belt system required. Installation will be scrutinized.

37.3 Approved helmet required. (Section 7--1.10)

## **38 ELIGIBILITY**

38.1 Season champion ineligible the following year.

38.2 Officials will resolve any eligibility questions.

38.3 Anyone 16 years of age and eligible for a driver's license with the exception of currently registered LM drivers may compete. **Ages 14-15 allowed with approval from Minor Eligibility Panel.**

38.4 Management reserves the right to accept or deny eligibility to anyone.

38.5 Roadrunner Challenge open to any driver.

## **39 GENERAL POLICY**

39.1 Tampering with another car or in any proven theft or dishonest act will result in suspension & arrest.

39.2 Always stay in car with belts and helmet on.

39.3 Car must be clean of glass and loose debris.

39.4 Illegal parts will be confiscated.

39.5 RoadRunners must have working scanner tuned to Official's frequency **469.875**

**40 NUMBERS & APPEARANCE**

- 40.1 A number at least 22" or more in height must appear on both sides in a contrasting color.
- 40.2 Cars must display roof top numbers 30" high, readable from the right side (scoring tower side).
- 40.3 Car number of at least 8" must be painted on right side (passenger side) windshield.
- 40.4 Number at least 6" must be painted on rear of car.
- 40.5 Can't be seen, can't be scored.

**41 TYPES OF RACING EVENTS**

- 41.1 At the discretion of the Management, different types of novelty events may be set up which will add to the color and competitive spirit of the race. You will be expected to compete.
- 41.2 Management may, at their discretion, alter direction, length and procedure of certain racing events

**42 MANAGEMENT CLAIM RULE**

There is no Claim Rule at this time.

**43 "BREAKOUT" rule**

---

There is no Breakout Rule at this time.

## WINGED WOMEN ON WHEELS

- ☒ All Bandit rules apply, they will run on the oval. Cars meeting Hornet rules also allowed.
- ☒ **WWoW cars must have metal wing on roof at least 18" wide**
- ☒ Separate division registration required.
- ☒ Seats, belts, and pedals must be fitted for driver and at appropriate lengths.
- ☒ Car may compete in Bandit Division, but "wing" must be removed.
- ☒ All procedures, general rules and policies stated in other sections of this rulebook apply, except in cases of obvious conflict.

## FIGURE 8

- ☒ Will follow RoadRunner Rules
- ☒ Management reserves the right to include and /or exclude vehicles.
- ☒ All cars must meet minimum specifications.
- ☒ Drivers door bar or door "plate" must be utilized.
- ☒ Racing type safety belts required: Suggested minimum is five point harness.
- ☒ Both front wheels must use racing type wheels.
- ☒ All wheels must have oversized lugs.
- ☒ Any driver may participate.
- ☒ Separate registration required.
- ☒ Any and all vehicles that are involved in "X" collisions are suspended for a minimum of one racing event.
- ☒ ROCKFORD SPEEDWAY MANAGEMENT RESERVES THE RIGHT TO CHANGE, ALTER, OMIT AND REPUBLISH (BY TECHNICAL BULLETIN) ALL FIGURE 8 RULES, TYPES OF CARS, EVENTS AND PROCEDURES

# **BANDITS**

## **COMPETING DURING WEDNESDAY NIGHT PROGRAMS**

### **CONSULT SECTION 7 FOR MINIMUM SPECIFICATIONS WHICH APPLY TO ALL RACING DIVISIONS**

This is a stock, unmodified, front wheel drive only 4 cylinder class. NOT NASCAR Sanctioned.

Absolutely NO modifications or enhancements other than what is specified by these rules will be allowed.

In certain rare circumstances where deviations from the rules do not give the car any advantage and may be more economical or practical, you may apply in writing for a waiver asking for an exemption.

This must be submitted to the designated track officials and approved before you compete.

#### **1. WHEELBASE AND ELIGIBLE MODELS**

- 1.1 Any front wheel drive only passenger car, minimum of 10 years old, with a wheelbase of 92" to 104"
- 1.2 NO Honda CRX's allowed.

#### **2 THE CAR AND BODY**

- 2.1 Factory OEM for make, model, and year with stock 4 cylinder engine.
- 2.2 Body, frame, floor pans must be complete and unmodified, except where rules allow trimming
- 2.3. No rear wheel drive cars or trucks
- 2.4. All doors must be welded, chained, or bolted shut
- 2.5. Hood and trunk must be secured with two or more hood pins
- 2.6 Plastic, trim, and items that could break, burn, or fall off, must be removed in and outside the car
- 2.7. Both bumpers must be stock, complete and mounted in stock position
- 2.8. Skirts, hood scoops front air dam and a 3" max height rear spoiler may be installed for cosmetic purposes only
- 2.9 Anything that can be unbolted (hinges, brackets, etc) may be removed
- 2.10 You may skin the hood/decklid
- 2.11 Can run after market nose cover over original stock bumper
- 2.12 1" maximum square tubing "rub rails" allowed between front and rear wheel wells. Ends must be chamfered and capped (no sharp edges)
- 2.13 Wheel openings may be trimmed for tire clearance.

#### **3 WINDSHIELD AND GLASS**

- 3.1 All glass (head, tail, and marker lights) except windshield, must be removed
- 3.2 You may replace the windshield with lexan
- 3.3 Lexan windshield requires a center brace inside

#### **DETAILED ENGINE SPECIFICATIONS**

#### **4 LOCATION**

- 4.1 Engine must be in original stock rubber mounts, in stock location.

#### **5 GENERAL ENGINE CHARACTERISTICS**

- 5.1 Strictly stock for make, models, 4 cylinder SOHC or DOHC engines (no turbos or superchargers)
- 5.2 No aftermarket performance parts
- 5.3. Air cleaner must be stock, unmodified
- 5.4. You may remove unnecessary parts and wiring (A/C compressors, smog pumps, etc)

#### **6 ENGINE DISPLACEMENT**

- 6.1 Stock stroke.
- 6.2 Overbore of .020 allowed for all makes.

#### **7 ENGINE BLOCK**

- 7.1 Engine block *exactly* as produced by manufacturer.

#### **8 ENGINE PISTONS**

- 8.1 Stock OEM ONLY.
- 8.2 No "made for racing" pistons.

8.3 Pistons must be the original or same as original.

## **9 OIL PAN**

9.1 Stock only, with NO additions or alterations.

## **10 CRANKSHAFT & BALANCER**

10.1 Stock only, replacement must be original OEM.

## **11 CYLINDER HEADS**

11.1 Stock Head only.

11.2 No after-market heads

11.3 No porting, polishing or gasket matching

11.4 Altered heads will be confiscated.

11.5 The stock listed valve size/configuration will be enforced

## **12 INTAKE MANIFOLD**

12.1 Must be unaltered stock for that make, model, engine.

## **13 CAMSHAFT, VALVE LIFTERS AND ROCKER ARMS**

13.1 Camshaft, lifters/followers rocker arms must be stock for that make model.

## **14 COMPRESSION**

14.1 Compression ratio may not be altered from stock.

## **15 EXHAUST**

15.1 Exhaust must run under the car, at least to behind the driver's seat

15.2. No flex pipe

15.3. Effective muffler required 100 decibels maximum @ 100 feet minimum.

15.4. No dual exhaust

## **16 CARBURETOR/FUEL INJECTION**

16.1 Must be stock production for that make, model, year.

## **17 CARBURETOR /THROTTLE BODY SPACERS**

17.1 Not allowed.

## **18 AIR INTAKE**

18.1 Air cleaner must be stock, with a non-reusable (paper) filter element

## **19 FUEL SYSTEM**

19.1 Stock OEM only.

## **20 ELECTRICAL / BATTERY**

20.1 You may relocate the battery. If in driver's compartment, must be covered with a marine case or similar

20.2. Battery must be securely mounted to chassis with steel straps.

20.3 Battery Kill Switch-Mandatory in center of car, MUST BE LABELLED. Must disable all electrical power to the car.

## **21 COOLING SYSTEM**

21.1 Stock OEM radiator in stock location.

21.2 Stock production overflow catch-can must be maintained inside engine compartment.

21.4 No extra engine coolers.

21.5 No antifreeze allowed.

## **22 CLUTCH --**

22.1 Stock clutch, pressure plate, and flywheel for that make, model, engine.

## **23 TRANSMISSIONS**

23.1 Stock production transaxle for that make, model.

23.2 Stock type shifter only.

## **24 DIFFERENTIAL**

24.1 Unaltered stock differential only.

24.2 No posi-traction or limited slips.

24.3 Only one wheel may drive.

## **25 DRIVELINE**

25.1 Must be front wheel drive.

25.2 Stock production axles only

## **26 BRAKES**

26.1. Must lock all four wheels

26.2 No aftermarket proportioning devices

26.3. Stock Brakes, pads, rotors, drums

26.4. No drilling

26.5. Stock components only

## **27 FRAMES**

27.1 Body and frame components must be the same. Must remain in original OEM configuration for that make and model.

27.2 Complete bumper-to-bumper stock frame and unibody must be retained.

27.3 Stub repairs must maintain OEM measurements.

27.4 Welding to OEM seams is allowed for rotted areas, but no reinforcing of suspension or tying into roll bars

## **28 ROLL BAR INSTALLATION**

28.1. Minimum four points around the driver 1 3/4" diameter .090" wall, mild steel. No exhaust tubing or water pipe.

28.2. Roll cage must be sufficiently welded to floor/rocker box, or welded to sandwich plate bolted to floor

28.3. Top of roll bar must be reinforced to the rear with two bars, either to spring towers or rear frame

28.4. Spring towers may be connected side to side, at both front and rear suspension.

28.5. Main roll bar behind driver must contain a diagonal bar

28.6. Minimum of 3 door bars, driver side and passenger side

28.7. Driver side door bars must be covered with steel deflector plate, 1/8" min. thickness

28.8. Minimum of 5 side to side bars:

a. top of main hoop

b. bottom of main hoop about 4" above floor

c. middle of main hoop directly behind seat

d. top front of cage by windshield, and

e. at front of cage at dash height

28.9. No bars through the front firewall, except recommended foot protection bar.

28.10. The cage must protect the driver and will be thoroughly inspected for safety

28.11. Use good common sense; consult persons experienced in building and welding

28.12. Safety padding must be installed around driver (door bars and roll cage bars)

28.13. You may skin door panels for installing roll cage

## **29 SUSPENSION**

29.1 Must remain stock for make, model, and year.

29.2. The only optional exceptions are as follows:

a. You may run camber on the front and rear wheels, **no limit**. You may only elongate existing adjustment points to accomplish this

b. You may heat or cut springs to lower the car. Except for exhaust components, minimum ground clearance is **4 1/4"** for any part, after the race

c. You may use any steel spring that fits in the stock location

d. Spring rubbers, clamps or threaded collars on springs not allowed

e. Sway bar links must be of equal length side to side, or disconnected

f. No adjustments to rear tow measurement.

## **30 SPINDLES**

30.1 Stock OEM spindles/knuckles only for that make and model

30.2 Oversized studs recommended.

### **31 Steering**

31.1 Stock steering systems only.

31.2 You may replace or modify the steering column to accommodate a removable wheel

### **32 GROUND CLEARANCE**

32.1 Frame rails must maintain a minimum ground clearance of 4-1/2 inches at all times, with driver in car.

### **33 WHEELS**

33.1 WHEELS MUST BE STEEL, MAX 6", ALL FOUR THE SAME DIAMETER (NO ALUMINUM OR MAGNESIUM)

33.2. You may run an aftermarket heavy-duty wheel, max 4" backspace from center

33.3. 1" lug nuts are required on the right wheels, it's encouraged to use them on all four

33.4 Lug nut threads must be visible on outside of lug nuts

33.5 Wheel spacers allowed, maximum thickness 3/8"

### **34 TIRES**

34.1 Tires must be same size/series per axle. Maximum 15" P195 Series maximum cost \$66

34.2. Track may claim any tire at any time for \$60-no questions asked

34.3 Any loss of a wheel or tire requires driver to immediately leave the race track

### **35 WEIGHT**

#### **Motor Size (in cc) Minimum weight**

35.1. 0 to 1999 **2200 lbs**

35.2. 2000 to 2299 **2300 lbs**

35.3. 2300 to 2600 **2400 lbs**

35.4. For 2 valve OHC engine **Add 25 lbs**

35.5. For 3 valve OHC engine **Add 75 lbs**

35.6. For 4 valve OHC engine **Add 100 lbs**

35.7. for VTech engine **Add another 100 lbs**

35.8. All weights include driver

35.9. All weights will be securely bolted to frame or cage, be painted white, and have car number on it

35.10. Any car with an apparent time advantage can and will be required to add additional weight in 100 lb increments

### **36 GAS TANK INSTALLATION**

36.1 Stock fuel tank located in front of rear wheels can be left there but must be secured with two extra metal straps

36.2. All other fuel tanks must be mounted in the trunk area between the rear wheels as far forward as possible

36.3. Tanks must be fastened with steel straps, bolts, and oversized washers

36.4. Filler spouts must face left

36.5. A complete steel firewall must be between the tank and the driver's compartment

36.6. Fuel cells are recommended, 8 gallon maximum, and must be mounted on top of floor pan

36.7. Fuel lines MAY NOT be run through the drivers compartment.

36.8. Fuel tank rupture or fuel spillage will draw an immediate black flag.

### **37 PERSONAL PROTECTION REQUIREMENTS**

37.1 Driver must wear full racing firesuit, gloves, & eye protection. No polyester clothing allowed.

37.2 Approved helmet required. (Section 7--1.10)

### **37 PERSONAL PROTECTION REQUIREMENTS continued**

37.3. Window Nets Mandatory with seat belt style release at front top cage upright

37.4. Fire Extinguisher Mandatory, securely mounted, fully charged, dial type

37.5. Tow Hooks-a secure towing device (hook, etc) MUST be in place both front and rear, securely fastened and located so as not to present a hazard in the event of contact

37.6 Five point 3" minimum width lap and shoulder harness, dated 2006 or newer. Crotch strap required.

37.7. Belts must be anchored to roll cage or OEM anchors. Belt anchors must swivel. Grade 5 hardware required.

- 37.8. Shoulder harness must not be anchored lower than 2" below driver's shoulder height
- 37.9. Aluminum racing seat required, securely fastened to cage or frame
- 37.10. Head rest support behind seat required
- 37.11. Shoulder supports and head supports on right and left sides of seat recommended
- 37.12 Drivers compartment must be sealed off from engine compartment and fuel container
- 37.13 Access to driver from right side by emergency personnel required

### **38 ELIGIBILITY**

- 38.3 Anyone 14 years of age or older may compete.
- 38.4 Management reserves the right to accept or deny eligibility to anyone.

### **39 GENERAL POLICY**

- 39.1 Tampering with another car or in any proven theft or dishonest act will result in suspension & arrest.
- 39.2 Always stay in car with belts and helmet on.
- 39.3 One driver per night. Only one person may hot lap and race the car during the event.
- 39.4 Car must be clean of glass and loose debris.
- 39.5 Illegal parts will be confiscated.
- 39.6 Bandits must have working scanner/ Raceceiver/Solo II tuned to channel 1591 (469.8750)

### **40 NUMBERS & APPEARANCE**

- 40.1 A number at least 18" or more in height must appear on both sides in a contrasting color.
- 40.2 Cars must display roof top numbers 24" high, readable from the left side
- 40.3 Car number of at least 4" must be displayed on right side (passenger side) windshield.
- 40.4 Number at least 4" must be displayed on rear of car.
- 40.5 Can't be seen, can't be scored.

### **41 TYPES OF RACING EVENTS**

- 41.1 At the discretion of the Management, different types of novelty events may be set up which will add to the color and competitive spirit of the race. You will be expected to compete.
- 41.2 Management may, at their discretion, alter direction, length and procedure of certain racing events

### **42 MANAGEMENT CLAIM RULE**

There is no Claim Rule at this time.

### **43 "BREAKOUT" rule**

There is no Breakout Rule at this time.

---

# ***HORNETS***

Driver Eligibility : No driver registered in another division may compete in this class. Previous year champion may not compete. **Additional drivers may also be declared ineligible.**

# Hornets are invited to compete with the Bandits, only if they run their Hornet car with Bandits

## Hornets will be competing in select 'non-Wed' events

Any 4 cylinder car, mini-van or station wagon with complete stock body, frame and suspension. **NO Honda CRX.** No bracing anywhere except inside the drivers' compartment (if roll bar equipped).

Dash, interior, steering and pedals must remain stock for that make and model. All insulation under hood and side mirrors must be removed. Loose interior items such as carpet and rear lower seat cushion may be removed.

Engine hood and trunk must open for inspection.

Car horns, car radios and speakers must remain intact and in working condition.

Stock carburetor/fuel injection system for that make and model. NO Turbo powered or all wheel drive cars.

Stock transmission, exhaust and unaltered rear end for that make and model.

Battery must remain under hood, be securely fastened and covered.

**Stock unaltered engine and rear end for that make and model. No V-Tech Engines**

Approved passenger car tires only. Tire width maximum of 195mm. Aspect ration of 70, 75, 78 only. ie: P195 75R14

Wheels must be maximum rim diameter 14", wheels and tires must be same type and/or offset on all four corners.

**NO low profile-type tires. Any tire may be disallowed at officials discretion at any time. Oversized lug nuts required on front hubs.**

Gas tanks: if stock gas tank is ahead of rear axle it may remain in place. If stock gas tank is behind rear axle, it must be replaced with a fuel cell or boat tank (max. of 6.6 gallons). Fuel cell/boat tank must be covered, secured by four metal straps and located in trunk.

Roll Bars (*not mandatory but recommended*) A single hoop roll bar accepted (see Roadrunner minimums) OR two (minimum of 3.5 inches) pipes with steel mounting plates on each end vertical from ceiling to floorboard allowed. Roll bars must be welded or bolted to car. Installation subject to approval by Technical Inspector.

Driver's door must be welded or chained shut. Driver side door plates recommended, but must remain flat with no catching edges (A leaf spring separated and fastened to the outside of the door allowed). Passenger door must be chained, however door must open when chain is removed.

Approved helmets, seat belts, gloves, window net, working fire extinguisher and firesuits required. No inertia reels. A minimum of a five-point 3" harness required.

a. Drivers seat may be replaced with any competition type seat that does not fold or move. If Stock seat is used it must be welded to prevent movement

b. Seat must mount to a steel substructure (track) that uses the stock floor mounting holes.

c. Seat mounting is subject to technical scrutiny.

All glass (except windshield) must be removed. Third brake light must remain intact and operable. All sun roofs must be covered with a minimum 1/8" steel plate.

NO anti-freeze allowed – drain before you reach the Speedway.

Cars **MUST** be painted bright yellow with a minimum of one black or red stripe. Cars not painted yellow will start at the rear of the field. Themed cars must be approved by Track Management. Car numbers on doors must be at least 18" tall in an easy to see contrasting color. Roof numbers must be at least 24" in height. Be prepared to change your number if necessary.

Bumpers may be chained. An 8" x 14" hole may be cut in hood. Hood must be secured by hood pins only.

**Must be age 14 or older to compete**

**Management claim in effect at all times for all cars. \$300 for cars WITHOUT a cage, \$400 for cars WITH a cage. Claims do not include personal safety equipment (net, harness, seat)**

# FLAG RULES

## A. GREEN FLAG

1. The starter will turn off the yellow caution lights and hold up 1 flag indicating “one to go” which means the race will start on the next lap. All cars are to close up, hold their position and speed set by the pace car. No “scrubbing of tires”, weaving, or other car movement is allowed. When the pace car leaves the racing surface, the pole position (inside front row) shall maintain the pace speed until the green flag is displayed.
2. At the discretion of the Race Director, any cars bumping, shoving, or holding up starting procedures will be given the “consultation” (black) flag and sent to the pits to speak with an official.
3. On the original start of the race, no passing is allowed until the lead car has crossed the start/finish line (or start line when used) under green. This is to avoid first lap accidents.
4. Any car passing or “jumping” position on any start shall be penalized two positions for every one position gained. The penalty shall be assessed at the next opportunity or end of the race. The driver may “give back” the position(s) before one lap is completed without penalty. If the “Pole” car moves from their position (pulling into the outside lane) before the start line, they will be penalized for jumping the start.
5. In most cases, one-half the starting field must complete a full lap for the race to be officially underway.
6. When a yellow or red flag is displayed before one lap is completed, the “original start flag” (red flag with white square in the middle) will be displayed. Drivers that are able to continue shall proceed to their original starting spot as quickly as possible.
7. On restarts, the lead car remains out front while all others line up double file behind the leader. Racing and passing may begin when the green flag/lights are displayed.
8. When the orange traffic cone is placed at the start/ finish line, all cars behind the leader must choose the high (outside) or low (inside) lane for their restart. Drivers must select a lane upon reaching the cone must stay in that lane until the green flag is displayed. Cars may gain positions by selecting the shortest lane. Cars changing lanes after the cone will be given the consultation flag to report to the pits. They may rejoin the field at the tail end of the longest line.
9. Leaders have the option of either lane. All others must remain behind the leader until the green is displayed. Passing is permitted after the green is displayed.
10. With 10 laps or less remaining in feature events, officials may implement single file restarts at their discretion, cars not up to racing speed or laps down will be sent to the tail end of the longest line on restarts.
11. Cars several laps down, damaged, or in the way may be given the consultation flag and sent to the pits.
12. Cars returning to the racing surface from the pits shall rejoin the rear of the field at the direction of the ramp official.

## B. YELLOW FLAG “CAUTION”

1. The yellow flag signifies a potential hazard on the race track and requires drivers to **slow** their vehicle as soon as possible.
2. Drivers do not race back to the yellow; they must maintain their position and slow to a cautious pace. The leader will be picked up by the pace car. All drivers shall close up on the pace car in a **single line** and await further instructions. Drivers shall follow the path taken by the pace car to avoid debris, liquid or other obstructions on the racing surface.
3. The racing lineup shall revert to the last completed lap as determined by scoring officials. The scoring officials have complete discretion to determine the positions of cars at the time and to reposition cars in accordance with their determination. Their word is final. If you dispute your position, pull to the inside of the car where you think you belong. Scoring will confirm your position, and a track official will direct you to your starting spot. Failure to quickly take your position will lead to a consultation flag, a trip to the pits, and rejoining the field at the tail of the longest line.
4. Yellow flag laps do not count unless specified in entry form or at drivers meeting.

5. The car or cars deemed as the cause of the caution will be restarted, if able, at the tail end of the longest line. Fault shall be a judgment call and the officials' decision is final. Fault may be described as, but not limited to; instigating the action, result of the action, or part of either.
6. If officials are unable to determine which car or cars were the cause of the caution, then all cars involved in the incident may be sent to the rear, or all cars will be returned to their position as of the last completed lap.
7. If a yellow flag is displayed for objects on the racing surface, spinouts, crashes, or other disruption to the lineup caused by liquid or other circumstances beyond anyone's control, then a "no-fault" caution shall be in effect and all cars able to continue will revert back to their position as of the last green flag lap.
8. Cars may not stop on the racing surface during a caution period. Cars needing repairs must enter the pits and have work completed there. Drivers may not stop in the infield and work on their car. All cars entering the pits shall rejoin the field at the tail end of the longest line.
9. Any car receiving assistance not directed by the Race Director, from any official, crewmember, or employee, on the racing surface or infield will be immediately disqualified. No service or repair may begin until the car has entered the pit area.
10. No one may enter the racing surface to perform repairs on any racing vehicle under the yellow or red flag. Cars receiving such service shall be immediately disqualified from the event.
11. Any car or cars that spin out by themselves, or by minor or incidental contact stop on or near the racing surface, or go into the infield must attempt to restart immediately and continue to race. The yellow flag will not be displayed if there is no apparent damage or the car is not positioned in an extremely hazardous position for one full lap. The car shall then rejoin the field at the tail end of the longest line.
12. Cars that cause a caution by themselves more than twice in the same race will be sent to the pits for the remainder of that race.
13. When a caution (pace) car is used, no car may pass the caution car, unless directed to do so by the caution car driver. Cars that pass the caution car without permission shall be given the consultation flag and report to the official in the pit area. Repeated violations of this rule will result in disqualification and /or suspension.
14. A "Gentleman's/Tap Out" rule will be used on a trial basis, if a driver feels they are solely at fault for an incident, they may pull to the bottom of the start/finish line and tap their roof, at that time only that driver will be sent to the tail of the longest line with all others deemed involved awarded their prior position.

#### **C. RED FLAG 'RACE STOPPED'**

1. When the red flag is displayed the driver shall get control of the racecar, reduce speed immediately and stop as directed by the pace car or on-track official. Cars failing to stop will be given the consultation flag and sent to the pits. A minimum of a one-lap penalty shall be given.
2. If yellow flags laps were counted, then no work may be performed on any vehicle in that event while in pit area unless directed to do so by the race director. Penalties will range from one lap to disqualification from the event.
3. Once all cars have stopped, no cars will be allowed to move from the racing surface without permission. No cars may enter the racing surface from the pits until the red flag period ends. A one-lap penalty shall be given to the car(s) that fail to comply.
4. Drivers shall remain in their cars unless directed by an official to exit. The driver, crew, officials, or anyone else may NOT make repairs, adjustments, or alterations during this time. EIRI Rule in effect. A minimum of one lap penalty shall be given to offenders.
5. All drivers must be ready to restart at the command of the starter. Lineup will revert to last completed lap for those able to continue that did not enter the pits. Any driver not ready to restart will be given the consultation flag and report to the pit official.

#### **D. MOVE-OVER FLAG (BLUE WITH DIAGONAL YELLOW STRIPE)**

1. The blue flag with a diagonal yellow stripe signifies that faster traffic (leaders) are overtaking cars being signaled and that cars being given this flag should be prepared to yield or "Move over" to faster traffic.
2. Any car deliberately ignoring the starters signal or attempts to hold up or block the leaders advance shall receive the black flag and report to the consultation official in the pit area.

#### **E. BLACK FLAG (CONSULTATION)**

1. The black flag means “go to pits immediately” and report to the NASCAR official at the bottom of the exit ramp. This does not mean disqualification; however failure to heed the black flag will result in disqualification, suspension or fine.
2. After receiving the black flag, scoring on that car will cease until a pit stop is made and the driver reports to the NASCAR official and is released. Driving to the infield after receiving a black flag does not satisfy the black flag requirement. You MUST report to the pits.
3. Any car entering the infield under racing conditions must exit the track on the same side of the track. If a car “cuts” a corner, that car will receive the black flag.
4. Any car with the hood, trunk or any loose parts which causes a hazard to other cars will receive the black flag.
5. Any car emitting excessive smoke will be black flagged.
6. Any car that “Breaks out” will be black flagged.
7. Display of Black and Red flags together signifies the end of practice.

#### **F. BLACK FLAG WITH WHITE CROSS (BUSCH FLAG)**

1. Any car that fails to report for a black flag will be shown the “Busch Flag.” The Busch Flag results in disqualification for the remainder of that race and entire event. Load up and go home.
2. Any car endangering the safety of others because of poor handling, reckless driving, defective equipment or rough driving shall be Busch Flagged.
3. Display of temper or other unsportsmanlike conduct will result in the Busch Flag.

#### **G. WHITE FLAG**

1. When the white flag is displayed, it means the leader has started their last lap.
2. The checkered flag will always follow the white flag.

#### **H. CHECKERED FLAG**

1. When the checkered flag is displayed it means the leader has completed the required distance and the race is over.
2. When the checkered flag is given to the leader, the rest of the field receives it on the same lap. Finishing positions will be paid according to the most laps traveled in the least amount of time, regardless of whether the car is running or not at the finish.
3. The driver receiving the checkered flag first must bring their car to the start line or area designated by the NASCAR official in charge. The driver and car must remain there until released by the NASCAR official. Failure to do so may result in a fine or disqualification.
4. If the lead car is intentionally spun by any car on the white flag lap, the official winner will be the car that was offended and the offender will be scored in last place.

#### **I. RED WITH WHITE SQUARE (REVERT TO ORIGINAL START)**

1. When a yellow or red flag have been displayed on the first lap, the “original start” flag will be displayed to signal drivers that they are to return to their original starting positions.
2. Any car that goes into the pits will always rejoin the field at the rear.

#### **J. MISCELLANEOUS**

1. Once you enter the racing surface for an event you are expected to be ready to race. If you enter the pits you must join the field at the rear.
2. All flags will be final. However, in extreme cases the starter may inadvertently display the wrong flag by mistake. It is the Race Directors decision to rescind the flag and revert back to the last completed green lap or carry on as if the flag were not displayed.
3. Do not stop on the track unless directed by officials or you are reporting a hazard or dangerous condition. Once directed to your starting spot, go there immediately.

4. These rules are amended when necessary and any bulletins take precedence

**K. BLOCKING**

1. Intentional blocking will not be tolerated. If the Race Director suspects you are holding up the progress of other cars, you will be signaled to pick a lane (high or low) Repeated acts of blocking will result in the Black flag.
2. Cars that continue to block after being warned will not be subject to checkered flag rule number 4.



